

Hersteller / *Manufacturer:*

**AS Medizintechnik GmbH**

Anschrift / *Address:*

Sattlerstr. 15  
78532 Tuttlingen / Germany

---

SRN-Nummer / *SRN-No.:*

DE-MF-000005601

Produktgruppe/ *Product group:*

Stanze / *Punches*

Artikel / *Articles:*

Siehe Anhang / *see annex*

Basis-UDI-DI / *Basic UDI-DI:*

4050123-40-0420-GF

Risikoklasse / *Risk class:*

Klasse Ir / *Class Ir*

Regel / *Rule:*

6

UMDNS:

15239 Stanze, sonstige / *Punches, Bone*

GMDN:

35441 *Spinal Rongeur*

EMDN:

L110699 Neurosurgery forceps, reusable - other

Zweckbestimmung / *Intended use:*

Scharfes chirurgisches Instrument mit dem Knochen und Knorpel bearbeitet werden kann.  
*Sharp surgical instrument with which bone and cartilage can be processed.*

Zertifikat / *Certificate:*

D1085600030

---

Mit der vorliegenden Konformitätserklärung erklären wir in alleiniger Verantwortung, dass das oben aufgeführte Medizinprodukt die grundlegenden Sicherheits- und Leistungsanforderungen gemäß Anhang I der Verordnung (EU) 2017/745 erfüllt.

*With the present Declaration of Conformity, we hereby declare under our sole responsibility, that the above-mentioned medical device meets the essential safety- and performance requirements, defined in annex I of the Regulation (EU) 2017/745.*

Das Konformitätsbewertungsverfahren wurde durchgeführt nach Anh. IX Kapitel I und III der Verordnung (EU) 2017/745 für Medizinprodukte.

*The Conformity Assessment Procedure has been performed according to annex IX, Chapter I and III of the Regulation (EU) 2017/745 for medical devices.*

Angewandte Spezifikationen für die die Konformität erklärt wird sind im FB 4.2.3.1 Liste Normen, Verordnungen und Gesetze aufgeführt.

*Applied specifications for which conformity is declared are listed in FB 4.2.3.1 List of standards, regulations and laws.*

Diese Erklärung verliert sofort ihre Gültigkeit in Folge jeder, nicht durch uns schriftlich autorisierten Änderung oder Reparatur am Produkt.

*This declaration becomes invalid immediately, when repairs or alterations occur to the product, without prior written approval by us.*

---

**Benannte Stelle:** Kennnummer: 0483  
 mdc medical device certification GmbH,  
 Kriegerstr. 6, 70191 Stuttgart

**Notified Body:** Identification number: 0483  
 mdc medical device certification GmbH,  
 Kriegerstr. 6, 70191 Stuttgart

Diese Erklärung ist gültig bis zum 19.07.2027  
 this declaration is valid until: 19.07.2027



Tuttlingen, den 13.03.2024

**Nino Schilling**  
 Geschäftsleitung / Managing Director

Anhang / Annex

Artikel-Nr. / Item number	Artikelbezeichnung deutsch	Articel description
26-794-00	Antrumstanze, nach oben schneidend, 2,5 x 7,0 mm, Schaft Ø 4,5 mm, NL 10 cm mit LL-Spülanschluss zur Innenreinigung	Antrum Punch, backwards cutting, up, 2,5 x 7,0 mm, Shaft Ø 4,5 mm, WL 10 cm with LL-connection to clean and rinse
26-794-01	Antrumstanze, nach rechts schneidend, 2,5 x 7,0 mm, Schaft Ø 4,5 mm, NL 10 cm mit LL-Spülanschluss zur Innenreinigung	Antrum Punch, backwards cutting, right, 2,5 x 7,0 mm, Shaft Ø 4,5 mm, WL 10 cm with LL-connection to clean and rinse
26-794-02	Antrumstanze, nach links schneidend, 2,5 x 7,0 mm, Schaft Ø 4,5 mm, NL 10 cm mit LL-Spülanschluss zur Innenreinigung	Antrum Punch, backwards cutting, left, 2,5 x 7,0 mm, Shaft Ø 4,5 mm, WL 10 cm with LL-connection to clean and rinse
26-794-03	Antrumstanze, nach unten schneidend, 2,5 x 7,0 mm, Schaft Ø 4,5 mm, NL 10 cm mit LL-Spülanschluss zur Innenreinigung	Antrum Punch, backwards cutting, down, 2,5 x 7,0 mm, Shaft Ø 4,5 mm, WL 10 cm with LL-connection to clean and rinse
26-794-10	Antrumstanze, nach oben schneidend, 1,5 x 5,0 mm, Schaft Ø 3,0 mm, NL 10 cm schlankes Modell für Kinder, LL-Spülans.	Antrum Punch, backwards cutting, up, 1,5 x 5,0 mm, Shaft Ø 3,0 mm, WL 10 cm delicate children model, LL-connection
26-794-11	Antrumstanze, nach rechts schneidend, 1,5 x 5,0 mm, Schaft Ø 3,0 mm, NL 10 cm schlankes Modell für Kinder, LL-Spülans.	Antrum Punch, backwards cutting, right, 1,5 x 5,0 mm, Shaft Ø 3,0 mm, WL 10 cm delicate children model, LL-connection
26-794-12	Antrumstanze, nach links schneidend, 1,5 x 5,0 mm, Schaft Ø 3,0 mm, NL 10 cm schlankes Modell für Kinder, LL-Spülans.	Antrum Punch, backwards cutting, left, 1,5 x 5,0 mm, Shaft Ø 3,0 mm, WL 10 cm delicate children model, LL-connection
26-794-13	Antrumstanze, nach unten schneidend, 1,5 x 5,0 mm, Schaft Ø 3,0 mm, NL 10 cm schlankes Modell für Kinder, LL-Spülans.	Antrum Punch, backwards cutting, down, 1,5 x 5,0 mm, Shaft Ø 3,0 mm, WL 10 cm delicate children model, LL-connection
26-796-00	Antrumstanze, 360° drehbar schneidend, 2,5 x 7,0 mm, Schaft Ø 3,5 mm, NL 10 cm mit LL-Spülanschluss zur Innenreinigung	Antrum Punch, 360° rotatable cutting, 2,5 x 7,0 mm, Shaft Ø 3,5 mm, WL 10 cm with LL-connection to clean and rinse
26-796-10	Antrumstanze, 360° drehbar schneidend, 1,5 x 5,0 mm, Schaft Ø 3,0 mm, NL 10 cm schlankes Modell für Kinder, LL-Spülans.	Antrum Punch, 360° rotatable cutting, 1,5 x 5,0 mm, Shaft Ø 3,0 mm, WL 10 cm delicate children model, LL-connection
26-798-02	Stirnhöhlenstanzen, 2 x 2,5 mm, aufgeb., nach oben schneidend, NL 13 cm	Frontal Sinus Punch, 2 x 2,5 mm, upward curved, up cutting, WL 13 cm
26-798-03	Stirnhöhlenstanzen, 3 x 3,5 mm, aufgeb., nach oben schneidend, NL 13 cm	Frontal Sinus Punch, 3 x 3,5 mm, upward curved, up cutting, WL 13 cm
26-798-05	Stirnhöhlenstanzen, 5 x 5,5 mm, aufgeb., nach oben schneidend, NL 13 cm	Frontal Sinus Punch, 5 x 5,5 mm, upward curved, up cutting, WL 13 cm
27-426-01	House-Dieter Hammerkopfstanze, 1,3 mm, nach unten schneidend, NL 80 mm	House-Dieter Malleus Nipper, 1,3 mm, down cutting, WL 80 mm
27-426-02	House-Dieter Hammerkopfstanze, 1,3 mm, nach oben schneidend, NL 80 mm	House-Dieter Malleus Nipper, 1,3 mm, up cutting, WL 80 mm
27-426-03	House-Dieter Hammerkopfstanze, 1,3 mm, nach links schneidend, NL 80 mm	House-Dieter Malleus Nipper, 1,3 mm, left cutting, WL 80 mm
27-426-04	House-Dieter Hammerkopfstanze, 1,3 mm, nach rechts schneidend, NL 80 mm	House-Dieter Malleus Nipper, 1,3 mm, right cutting, WL 80 mm
40-000-22	Citelli Knochenstanze, 65 mm, 2mm, 90° up	Citelli Punch, 65 mm, 2 mm, 90° up
40-000-30	Citelli Knochenstanze, 65 mm, 3mm, 90° up	Citelli Punch, 65 mm, 3 mm, 90° up
40-002-10	Citelli-Beyer Stanze, 95 mm, 1,0 mm, 90° up	Citelli-Beyer Punch, 95 mm, 1,0 mm, 90° up

40-002-18	Citelli-Beyer Stanze, 95 mm, 1,8 mm, 90°up	Citelli-Beyer Punch, 95 mm, 1,8 mm, 90°up
40-004-03	Kerrison Stanze, 90 mm, 3 mm, 90° up	Kerrison Punch, 90 mm, 3 mm, 90° up
40-004-04	Kerrison Stanze, 90 mm, 4 mm, 90° up	Kerrison Punch, 90 mm, 4 mm, 90° up
40-004-05	Kerrison Stanze, 90 mm, 5 mm, 90° up	Kerrison Punch, 90 mm, 5 mm, 90° up
40-004-06	Kerrison Stanze, 90 mm, 6 mm, 90° up	Kerrison Punch, 90 mm, 6 mm, 90° up
40-005-20	Hajek-Claus Stanze, 20 cm	Hajek-Claus Punch, 20 cm
40-006-33	Hajek-Kofler Stanze, 140 mm, 3,3 mm, 90°up	Hajek-Kofler Punch, 140 mm, 3,3 mm, 90°up
40-006-40	Hajek-Kofler Stanze, 140 mm, 4,0 mm, 90°up	Hajek-Kofler Punch, 140 mm, 4,0 mm, 90°up
40-007-33	Hajek-Kofler Stanze, 140 mm, 3,3 mm, 90°down	Hajek-Kofler Punch, 140 mm, 3,3 mm, 90°down
40-007-40	Hajek-Kofler Stanze, 140 mm, 4,0 mm, 90°down	Hajek-Kofler Punch, 140 mm, 4,0 mm, 90°down
40-009-40	Hajek-Kofler Stanze, 170 mm, 3,5 mm, 90°360° drehbar	Hajek-Kofler Punch, 170 mm, 3,5 mm, 90°360° rotatable
40-014-01	Kerrison Stanze, 180 mm, 1 mm, 40° up	Kerrison Punch, 180 mm, 1 mm, 40° up
40-014-01 B	Kerrison Stanze, 180 mm, 1 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 180 mm, 1 mm, 40° upwith ceramic coating
40-014-01 BF	Kerrison Stanze, 180 mm, 1 mm, 40° upmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 180 mm, 1 mm, 40° upwith ceramic coating and thin footplate
40-014-01 F	Kerrison Stanze, 180 mm, 1 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 180 mm, 1 mm, 40° upwith thin footplate
40-014-01 Z	Kerrison Stanze, 180 mm, 1 mm, 40° upzerlegbar	Kerrison Punch, 180 mm, 1 mm, 40° updetachable
40-014-01 ZB	Kerrison Stanze, 180 mm, 1 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 180 mm, 1 mm, 40° updetachable, with ceramic coating
40-014-01 ZBF	Kerrison Stanze, 180 mm, 1 mm, 40° upzerlegbar, mit Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 180 mm, 1 mm, 40° updetachable, with ceramic coating andthin footplate
40-014-01 ZF	Kerrison Stanze, 180 mm, 1 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 180 mm, 1 mm, 40° updetachable, with thin footplate
40-014-02	Kerrison Stanze, 180 mm, 2 mm, 40° up	Kerrison Punch, 180 mm, 2 mm, 40° up
40-014-02 B	Kerrison Stanze, 180 mm, 2 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 180 mm, 2 mm, 40° upwith ceramic coating
40-014-02 BE	Kerrison Stanze, 180 mm, 2 mm, 40° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 180 mm, 2 mm, 40° upwith ceramic coating and Ejector
40-014-02 BF	Kerrison Stanze, 180 mm, 2 mm, 40° upmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 180 mm, 2 mm, 40° upwith ceramic coating and thin footplate
40-014-02 F	Kerrison Stanze, 180 mm, 2 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 180 mm, 2 mm, 40° upwith thin footplate
40-014-02 FE	Kerrison Stanze, 180 mm, 2 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 2 mm, 40° upwith thin footplate and Ejector
40-014-02 Z	Kerrison Stanze, 180 mm, 2 mm, 40° upzerlegbar	Kerrison Punch, 180 mm, 2 mm, 40° updetachable
40-014-02 ZE	Kerrison Stanze, 180 mm, 2 mm, 40° up zerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 2 mm, 40° up detachable, with Ejector
40-014-02 ZB	Kerrison Stanze, 180 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 180 mm, 2 mm, 40° updetachable, with ceramic coating
40-014-02 ZBE	Kerrison Stanze, 180 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtung,und Auswerfer	Kerrison Punch, 180 mm, 2 mm, 40° updetachable, with ceramic coating,and Ejector
40-014-02 ZBF	Kerrison Stanze, 180 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtung,mit dünner Fußplatte	Kerrison Punch, 180 mm, 2 mm, 40° updetachable, with ceramic coating,with thin footplate
40-014-02 ZF	Kerrison Stanze, 180 mm, 2 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 180 mm, 2 mm, 40° updetachable, with thin footplate
40-014-03	Kerrison Stanze, 180 mm, 3 mm, 40° up	Kerrison Punch, 180 mm, 3 mm, 40° up
40-014-03 B	Kerrison Stanze, 180 mm, 3 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 180 mm, 3 mm, 40° upwith ceramic coating
40-014-03 BE	Kerrison Stanze, 180 mm, 3 mm, 40° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 40° upwith ceramic coating and Ejector
40-014-03 BF	Kerrison Stanze, 180 mm, 3 mm, 40° upmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 180 mm, 3 mm, 40° upwith ceramic coating and thin footplate
40-014-03 BFE	Kerrison Stanze, 180 mm, 3 mm, 40° upmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 40° upwith ceramic coating, thin footplate andEjector
40-014-03 E	Kerrison Stanze, 180 mm, 3 mm, 40° upmit Auswerfer	Kerrison Punch, 180 mm, 3 mm, 40° upwith Ejector
40-014-03 F	Kerrison Stanze, 180 mm, 3 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 180 mm, 3 mm, 40° upwith thin footplate
40-014-03 FE	Kerrison Stanze, 180 mm, 3 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 40° upwith thin footplate and Ejector
40-014-03 Z	Kerrison Stanze, 180 mm, 3 mm, 40° upzerlegbar	Kerrison Punch, 180 mm, 3 mm, 40° updetachable
40-014-03 ZB	Kerrison Stanze, 180 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 180 mm, 3 mm, 40° updetachable, with ceramic coating

40-014-03 ZBE	Kerrison Stanze, 180 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 40° updetachable, with ceramic coating, and Ejector
40-014-03 ZBF	Kerrison Stanze, 180 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte	Kerrison Punch, 180 mm, 3 mm, 40° updetachable, with ceramic coating, with thin footplate
40-014-03 ZBFE	Kerrison Stanze, 180 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 40° updetachable, with ceramic coating, with thin footplate and Ejector
40-014-03 ZE	Kerrison Stanze, 180 mm, 3 mm, 40° upzerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 3 mm, 40° updetachable, with Ejector
40-014-03 ZF	Kerrison Stanze, 180 mm, 3 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 180 mm, 3 mm, 40° updetachable, with thin footplate
40-014-03 ZFE	Kerrison Stanze, 180 mm, 3 mm, 40° upzerlegbar, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 40° updetachable, with thin footplate and Ejector
40-014-04	Kerrison Stanze, 180 mm, 4 mm, 40° up	Kerrison Punch, 180 mm, 4 mm, 40° up
40-014-04 B	Kerrison Stanze, 180 mm, 4 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 180 mm, 4 mm, 40° upwith ceramic coating
40-014-04 BE	Kerrison Stanze, 180 mm, 4 mm, 40° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 40° upwith ceramic coating and Ejector
40-014-04 BFE	Kerrison Stanze, 180 mm, 4 mm, 40° upmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 40° upwith ceramic coating, thin footplate and Ejector
40-014-04 E	Kerrison Stanze, 180 mm, 4 mm, 40° upmit Auswerfer	Kerrison Punch, 180 mm, 4 mm, 40° upwith Ejector
40-014-04 F	Kerrison Stanze, 180 mm, 4 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 180 mm, 4 mm, 40° upwith thin footplate
40-014-04 FE	Kerrison Stanze, 180 mm, 4 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 40° upwith thin footplate and Ejector
40-014-04 Z	Kerrison Stanze, 180 mm, 4 mm, 40° upzerlegbar	Kerrison Punch, 180 mm, 4 mm, 40° updetachable
40-014-04 ZB	Kerrison Stanze, 180 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 180 mm, 4 mm, 40° updetachable, with ceramic coating
40-014-04 ZBE	Kerrison Stanze, 180 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 40° updetachable, with ceramic coating, and Ejector
40-014-04 ZBF	Kerrison Stanze, 180 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte	Kerrison Punch, 180 mm, 4 mm, 40° updetachable, with ceramic coating, with thin footplate
40-014-04 ZBFE	Kerrison Stanze, 180 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 40° updetachable, with ceramic coating, with thin footplate and Ejector
40-014-04 ZE	Kerrison Stanze, 180 mm, 4 mm, 40° upzerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 4 mm, 40° updetachable, with Ejector
40-014-04 ZF	Kerrison Stanze, 180 mm, 4 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 180 mm, 4 mm, 40° updetachable, with thin footplate
40-014-04 ZFE	Kerrison Stanze, 180 mm, 4 mm, 40° upzerlegbar, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 40° updetachable, with thin footplate and Ejector
40-014-05	Kerrison Stanze, 180 mm, 5 mm, 40° up	Kerrison Punch, 180 mm, 5 mm, 40° up
40-014-05 B	Kerrison Stanze, 180 mm, 5 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 180 mm, 5 mm, 40° upwith ceramic coating
40-014-05 BE	Kerrison Stanze, 180 mm, 5 mm, 40° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 180 mm, 5 mm, 40° upwith ceramic coating and Ejector
40-014-05 BFE	Kerrison Stanze, 180 mm, 5 mm, 40° upmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 180 mm, 5 mm, 40° upwith ceramic coating, thin footplate and Ejector
40-014-05 E	Kerrison Stanze, 180 mm, 5 mm, 40° upmit Auswerfer	Kerrison Punch, 180 mm, 5 mm, 40° upwith Ejector
40-014-05 F	Kerrison Stanze, 180 mm, 5 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 180 mm, 5 mm, 40° upwith thin footplate
40-014-05 FE	Kerrison Stanze, 180 mm, 5 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 5 mm, 40° upwith thin footplate and Ejector
40-014-05 Z	Kerrison Stanze, 180 mm, 5 mm, 40° upzerlegbar	Kerrison Punch, 180 mm, 5 mm, 40° updetachable
40-014-05 ZB	Kerrison Stanze, 180 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 180 mm, 5 mm, 40° updetachable, with ceramic coating
40-014-05 ZBE	Kerrison Stanze, 180 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 180 mm, 5 mm, 40° updetachable, with ceramic coating, and Ejector
40-014-05 ZBF	Kerrison Stanze, 180 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte	Kerrison Punch, 180 mm, 5 mm, 40° updetachable, with ceramic coating, with thin footplate
40-014-05 ZBFE	Kerrison Stanze, 180 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 5 mm, 40° updetachable, with ceramic coating, with thin footplate and Ejector
40-014-05 ZE	Kerrison Stanze, 180 mm, 5 mm, 40° upzerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 5 mm, 40° updetachable, with Ejector
40-014-05 ZF	Kerrison Stanze, 180 mm, 5 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 180 mm, 5 mm, 40° updetachable, with thin footplate

40-014-05 ZFE	Kerrison Stanze, 180 mm, 5 mm, 40° upzerlegbar, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 5 mm, 40° updetachable, with thin footplate and Ejector
40-014-06	Kerrison Stanze, 180 mm, 6 mm, 40° up	Kerrison Punch, 180 mm, 6 mm, 40° up
40-014-06 BE	Kerrison Stanze, 180 mm, 6 mm, 40° up mit Keramikbeschichtung und Auswerfer	Kerrison Punch, 180 mm, 6 mm, 40° up with ceramic coating and Ejector
40-014-06 E	Kerrison Stanze, 180 mm, 6 mm, 40° up mit Auswerfer	Kerrison Punch, 180 mm, 6 mm, 40° up with Ejector
40-014-06 FE	Kerrison Stanze, 180 mm, 6 mm, 40° up mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 6 mm, 40° up with thin footplate and Ejector
40-014-06 Z	Kerrison Stanze, 180 mm, 6 mm, 40° upzerlegbar	Kerrison Punch, 180 mm, 6 mm, 40° updetachable
40-014-06 ZB	Kerrison Stanze, 180 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 180 mm, 6 mm, 40° updetachable, with ceramic coating
40-014-06 ZBE	Kerrison Stanze, 180 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 180 mm, 6 mm, 40° updetachable, with ceramic coating, and Ejector
40-014-06 ZBF	Kerrison Stanze, 180 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte	Kerrison Punch, 180 mm, 6 mm, 40° updetachable, with ceramic coating, with thin footplate
40-014-06 ZBFE	Kerrison Stanze, 180 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 6 mm, 40° updetachable, with ceramic coating, with thin footplate and Ejector
40-014-06 ZE	Kerrison Stanze, 180 mm, 6 mm, 40° upzerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 6 mm, 40° updetachable, with Ejector
40-014-06 ZF	Kerrison Stanze, 180 mm, 6 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 180 mm, 6 mm, 40° updetachable, with thin footplate
40-014-06 ZFE	Kerrison Stanze, 180 mm, 6 mm, 40° upzerlegbar, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 6 mm, 40° updetachable, with thin footplate and Ejector
40-014-11	Kerrison Stanze, 200 mm, 1 mm, 40° up	Kerrison Punch, 200 mm, 1 mm, 40° up
40-014-11 B	Kerrison Stanze, 200 mm, 1 mm, 40° up mit Keramikbeschichtung	Kerrison Punch, 200 mm, 1 mm, 40° up with ceramic coating
40-014-11 BF	Kerrison Stanze, 200 mm, 1 mm, 40° up mit Keramikbeschichtung und dünner Fußplatte	Kerrison Punch, 200 mm, 1 mm, 40° up with ceramic coating and thin footplate
40-014-11 F	Kerrison Stanze, 200 mm, 1 mm, 40° up mit dünner Fußplatte	Kerrison Punch, 200 mm, 1 mm, 40° up with thin footplate
40-014-11 Z	Kerrison Stanze, 200 mm, 1 mm, 40° upzerlegbar	Kerrison Punch, 200 mm, 1 mm, 40° updetachable
40-014-11 ZB	Kerrison Stanze, 200 mm, 1 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 200 mm, 1 mm, 40° updetachable, with ceramic coating
40-014-11 ZBF	Kerrison Stanze, 200 mm, 1 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte	Kerrison Punch, 200 mm, 1 mm, 40° updetachable, with ceramic coating, with thin footplate
40-014-11 ZF	Kerrison Stanze, 200 mm, 1 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 200 mm, 1 mm, 40° updetachable, with thin footplate
40-014-12	Kerrison Stanze, 200 mm, 2 mm, 40° up	Kerrison Punch, 200 mm, 2 mm, 40° up
40-014-12 B	Kerrison Stanze, 200 mm, 2 mm, 40° up mit Keramikbeschichtung	Kerrison Punch, 200 mm, 2 mm, 40° up with ceramic coating
40-014-12 BE	Kerrison Stanze, 200 mm, 2 mm, 40° up mit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 200 mm, 2 mm, 40° up with ceramic coating, and Ejector
40-014-12 BF	Kerrison Stanze, 200 mm, 2 mm, 40° up mit Keramikbeschichtung und dünner Fußplatte	Kerrison Punch, 200 mm, 2 mm, 40° up with ceramic coating and thin footplate
40-014-12 BFE	Kerrison Stanze, 200 mm, 2 mm, 40° up mit Keramikbeschichtung, dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 2 mm, 40° up with ceramic coating, thin footplate and Ejector
40-014-12 E	Kerrison Stanze, 200 mm, 2 mm, 40° up mit Auswerfer	Kerrison Punch, 200 mm, 2 mm, 40° up with Ejector
40-014-12 F	Kerrison Stanze, 200 mm, 2 mm, 40° up mit dünner Fußplatte	Kerrison Punch, 200 mm, 2 mm, 40° up with thin footplate
40-014-12 FE	Kerrison Stanze, 200 mm, 2 mm, 40° up mit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 2 mm, 40° up with thin footplate and Ejector
40-014-12 Z	Kerrison Stanze, 200 mm, 2 mm, 40° upzerlegbar	Kerrison Punch, 200 mm, 2 mm, 40° updetachable
40-014-12 ZB	Kerrison Stanze, 200 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 200 mm, 2 mm, 40° updetachable, with ceramic coating
40-014-12 ZBF	Kerrison Stanze, 200 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtung, und dünner Fußplatte	Kerrison Punch, 200 mm, 2 mm, 40° updetachable, with ceramic coating and thin footplate
40-014-12 ZBFE	Kerrison Stanze, 200 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 2 mm, 40° updetachable, with ceramic coating, with thin footplate and Ejector
40-014-12 ZE	Kerrison Stanze, 200 mm, 2 mm, 40° upzerlegbar mit Auswerfer	Kerrison Punch, 200 mm, 2 mm, 40° updetachable with Ejector
40-014-12 ZF	Kerrison Stanze, 200 mm, 2 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 200 mm, 2 mm, 40° updetachable, with thin footplate
40-014-125 BFE	Kerrison Stanze, 200 mm, 2,5 mm, 40° up mit Keramikbeschichtung, dünner Fußplatte, Auswerfer und Führung	Kerrison Punch, 200 mm, 2,5 mm, 40° up with ceramic coating, thin footplate, Ejector and guide
40-014-13	Kerrison Stanze, 200 mm, 3 mm, 40° up	Kerrison Punch, 200 mm, 3 mm, 40° up

40-014-13 B	Kerrison Stanze, 200 mm, 3 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 200 mm, 3 mm, 40° upwith ceramic coating
40-014-13 BE	Kerrison Stanze, 200 mm, 3 mm, 40° upmit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° upwith ceramic coating, and Ejector
40-014-13 BFE	Kerrison Stanze, 200 mm, 3 mm, 40° upmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° upwith ceramic coating, thin footplate andEjector
40-014-13 E	Kerrison Stanze, 200 mm, 3 mm, 40° upmit Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° upwith Ejector
40-014-13 F	Kerrison Stanze, 200 mm, 3 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 200 mm, 3 mm, 40° upwith thin footplate
40-014-13 FE	Kerrison Stanze, 200 mm, 3 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° upwith thin footplate and Ejector
40-014-13 Z	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar	Kerrison Punch, 200 mm, 3 mm, 40° updetachable
40-014-13 ZB	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 200 mm, 3 mm, 40° updetachable, with ceramic coating
40-014-13 ZBE	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtungund Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° updetachable, with ceramic coating andEjector
40-014-13 ZBF	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung,und dünner Fußplatte	Kerrison Punch, 200 mm, 3 mm, 40° updetachable, with ceramic coatingand thin footplate
40-014-13 ZBFE	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung,mit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° updetachable, with ceramic coating,with thin footplate and Ejector
40-014-13 ZE	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar mit Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° updetachable with Ejector
40-014-13 ZF	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 200 mm, 3 mm, 40° updetachable, with thin footplate
40-014-13 ZFE	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 200 mm, 3 mm, 40° updetachable, with thin footplate andEjector
40-014-14	Kerrison Stanze, 200 mm, 4 mm, 40° up	Kerrison Punch, 200 mm, 4 mm, 40° up
40-014-14 B	Kerrison Stanze, 200 mm, 4 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 200 mm, 4 mm, 40° upwith ceramic coating
40-014-14 BE	Kerrison Stanze, 200 mm, 4 mm, 40° upmit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 200 mm, 4 mm, 40° upwith ceramic coating, and Ejector
40-014-14 BFE	Kerrison Stanze, 200 mm, 4 mm, 40° upmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 200 mm, 4 mm, 40° upwith ceramic coating, thin footplate andEjector
40-014-14 E	Kerrison Stanze, 200 mm, 4 mm, 40° upmit Auswerfer	Kerrison Punch, 200 mm, 4 mm, 40° upwith Ejector
40-014-14 F	Kerrison Stanze, 200 mm, 4 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 200 mm, 4 mm, 40° upwith thin footplate
40-014-14 FE	Kerrison Stanze, 200 mm, 4 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 4 mm, 40° upwith thin footplate and Ejector
40-014-14 Z	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar	Kerrison Punch, 200 mm, 4 mm, 40° updetachable
40-014-14 ZB	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 200 mm, 4 mm, 40° updetachable, with ceramic coating
40-014-14 ZBE	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtungund Auswerfer	Kerrison Punch, 200 mm, 4 mm, 40° updetachable, with ceramic coating andEjector
40-014-14 ZBF	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung,und dünner Fußplatte	Kerrison Punch, 200 mm, 4 mm, 40° updetachable, with ceramic coatingand thin footplate
40-014-14 ZBFE	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung,mit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 4 mm, 40° updetachable, with ceramic coating,with thin footplate and Ejector, M-Model
40-014-14 ZE	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar mit Auswerfer	Kerrison Punch, 200 mm, 4 mm, 40° updetachable with Ejector
40-014-14 ZF	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 200 mm, 4 mm, 40° updetachable, with thin footplate
40-014-14 ZFE	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 200 mm, 4 mm, 40° updetachable, with thin footplate andEjector
40-014-15	Kerrison Stanze, 200 mm, 5 mm, 40° up	Kerrison Punch, 200 mm, 5 mm, 40° up
40-014-15 B	Kerrison Stanze, 200 mm, 5 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 200 mm, 5 mm, 40° upwith ceramic coating
40-014-15 BE	Kerrison Stanze, 200 mm, 5 mm, 40° upmit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 200 mm, 5 mm, 40° upwith ceramic coating, and Ejector
40-014-15 BFE	Kerrison Stanze, 200 mm, 5 mm, 40° upmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 200 mm, 5 mm, 40° upwith ceramic coating, thin footplate andEjector
40-014-15 E	Kerrison Stanze, 200 mm, 5 mm, 40° upmit Auswerfer	Kerrison Punch, 200 mm, 5 mm, 40° upwith Ejector
40-014-15 F	Kerrison Stanze, 200 mm, 5 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 200 mm, 5 mm, 40° upwith thin footplate

40-014-15 FE	Kerrison Stanze, 200 mm, 5 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 5 mm, 40° upwith thin footplate and Ejector
40-014-15 Z	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar	Kerrison Punch, 200 mm, 5 mm, 40° updetachable
40-014-15 ZB	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 200 mm, 5 mm, 40° updetachable, with ceramic coating
40-014-15 ZBE	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtungund Auswerfer	Kerrison Punch, 200 mm, 5 mm, 40° updetachable, with ceramic coating andEjector
40-014-15 ZBF	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtung,und dünner Fußplatte	Kerrison Punch, 200 mm, 5 mm, 40° updetachable, with ceramic coatingand thin footplate
40-014-15 ZBFE	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtung,mit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 5 mm, 40° updetachable, with ceramic coating,with thin footplate and Ejector
40-014-15 ZE	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar mit Auswerfer	Kerrison Punch, 200 mm, 5 mm, 40° updetachable with Ejector
40-014-15 ZF	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 200 mm, 5 mm, 40° updetachable, with thin footplate
40-014-15 ZFE	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 200 mm, 5 mm, 40° updetachable, with thin footplate andEjector
40-014-16	Kerrison Stanze, 200 mm, 6 mm, 40° up	Kerrison Punch, 200 mm, 6 mm, 40° up
40-014-16 B	Kerrison Stanze, 200 mm, 6 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 200 mm, 6 mm, 40° upwith ceramic coating
40-014-16 BFE	Kerrison Stanze, 200 mm, 6 mm, 40° upmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 200 mm, 6 mm, 40° upwith ceramic coating, thin footplate andEjector
40-014-16 F	Kerrison Stanze, 200 mm, 6 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 200 mm, 6 mm, 40° upwith thin footplate
40-014-16 Z	Kerrison Stanze, 200 mm, 6 mm, 40° upzerlegbar	Kerrison Punch, 200 mm, 6 mm, 40° updetachable
40-014-16 ZB	Kerrison Stanze, 200 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 200 mm, 6 mm, 40° updetachable, with ceramic coating
40-014-16 ZBE	Kerrison Stanze, 200 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtungund Auswerfer	Kerrison Punch, 200 mm, 6 mm, 40° updetachable, with ceramic coating andEjector
40-014-16 ZBF	Kerrison Stanze, 200 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtung,und dünner Fußplatte	Kerrison Punch, 200 mm, 6 mm, 40° updetachable, with ceramic coatingand thin footplate
40-014-16 ZBFE	Kerrison Stanze, 200 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtung,mit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 6 mm, 40° updetachable, with ceramic coating,with thin footplate and Ejector
40-014-16 ZE	Kerrison Stanze, 200 mm, 6 mm, 40° upzerlegbar mit Auswerfer	Kerrison Punch, 200 mm, 6 mm, 40° updetachable with Ejector
40-014-16 ZF	Kerrison Stanze, 200 mm, 6 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 200 mm, 6 mm, 40° updetachable, with thin footplate
40-014-16 ZFE	Kerrison Stanze, 200 mm, 6 mm, 40° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 200 mm, 6 mm, 40° updetachable, with thin footplate andEjector
40-014-21	Kerrison Stanze, 230 mm, 1 mm, 40° up	Kerrison Punch, 230 mm, 1 mm, 40° up
40-014-21 B	Kerrison Stanze, 230 mm, 1 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 1 mm, 40° upwith ceramic coating
40-014-21 F	Kerrison Stanze, 230 mm, 1 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 1 mm, 40° upwith thin footplate
40-014-21 Z	Kerrison Stanze, 230 mm, 1 mm, 40° upzerlegbar	Kerrison Punch, 230 mm, 1 mm, 40° updetachable
40-014-21 ZB	Kerrison Stanze, 230 mm, 1 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 230 mm, 1 mm, 40° updetachable, with ceramic coating
40-014-21 ZBF	Kerrison Stanze, 230 mm, 1 mm, 40° upzerlegbar, mit Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 230 mm, 1 mm, 40° updetachable, with ceramic coatingand thin footplate
40-014-21 ZF	Kerrison Stanze, 230 mm, 1 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 230 mm, 1 mm, 40° updetachable, with thin footplate
40-014-22	Kerrison Stanze, 230 mm, 2 mm, 40° up	Kerrison Punch, 230 mm, 2 mm, 40° up
40-014-22 B	Kerrison Stanze, 230 mm, 2 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 2 mm, 40° upwith ceramic coating
40-014-22 BF	Kerrison Stanze, 230 mm, 2 mm, 40° upmit Keramikbeschichtung unddünner Fußplatte	Kerrison Punch, 230 mm, 2 mm, 40° upwith ceramic coating and thin footplate
40-014-22 F	Kerrison Stanze, 230 mm, 2 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 2 mm, 40° upwith thin footplate
40-014-22 Z	Kerrison Stanze, 230 mm, 2 mm, 40° upzerlegbar	Kerrison Punch, 230 mm, 2 mm, 40° updetachable
40-014-22 ZB	Kerrison Stanze, 230 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 230 mm, 2 mm, 40° updetachable, with ceramic coating
40-014-22 ZBF	Kerrison Stanze, 230 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 230 mm, 2 mm, 40° updetachable, with ceramic coatingand thin footplate
40-014-22 ZBFE	Kerrison Stanze, 230 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtungdünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 2 mm, 40° updetachable, with ceramic coatingthin footplate and Ejector

40-014-22 ZF	Kerrison Stanze, 230 mm, 2 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 230 mm, 2 mm, 40° updetachable, with thin footplate
40-014-23	Kerrison Stanze, 230 mm, 3 mm, 40° up	Kerrison Punch, 230 mm, 3 mm, 40° up
40-014-23 B	Kerrison Stanze, 230 mm, 3 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 3 mm, 40° upwith ceramic coating
40-014-23 BE	Kerrison Stanze, 230 mm, 3 mm, 40° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 230 mm, 3 mm, 40° upwith ceramic coating and Ejector
40-014-23 BF	Kerrison Stanze, 230 mm, 3 mm, 40° upmit Keramikbeschichtung und dünner Fußplatte	Kerrison Punch, 230 mm, 3 mm, 40° upwith ceramic coating and thin footplate
40-014-23 BFE	Kerrison Stanze, 230 mm, 3 mm, 40° upmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 230 mm, 3 mm, 40° upwith ceramic coating, thin footplate and Ejector
40-014-23 E	Kerrison Stanze, 230 mm, 3 mm, 40° upmit Auswerfer	Kerrison Punch, 230 mm, 3 mm, 40° upwith Ejector
40-014-23 F	Kerrison Stanze, 230 mm, 3 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 3 mm, 40° upwith thin footplate
40-014-23 FE	Kerrison Stanze, 230 mm, 3 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 3 mm, 40° upwith thin footplate and Ejector
40-014-23 Z	Kerrison Stanze, 230 mm, 3 mm, 40° upzerlegbar	Kerrison Punch, 230 mm, 3 mm, 40° updetachable
40-014-23 ZB	Kerrison Stanze, 230 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 230 mm, 3 mm, 40° updetachable, with ceramic coating
40-014-23 ZBE	Kerrison Stanze, 230 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung und Auswerfer	Kerrison Punch, 230 mm, 3 mm, 40° updetachable, with ceramic coating and Ejector
40-014-23 ZBF	Kerrison Stanze, 230 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung und dünner Fußplatte	Kerrison Punch, 230 mm, 3 mm, 40° updetachable, with ceramic coating and thin footplate
40-014-23 ZBFE	Kerrison Stanze, 230 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 3 mm, 40° updetachable, with ceramic coating thin footplate and Ejector
40-014-23 ZE	Kerrison Stanze, 230 mm, 3 mm, 40° upzerlegbar, mit Auswerfer	Kerrison Punch, 230 mm, 3 mm, 40° updetachable, with Ejector
40-014-23 ZF	Kerrison Stanze, 230 mm, 3 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 230 mm, 3 mm, 40° updetachable, with thin footplate
40-014-23 ZFE	Kerrison Stanze, 230 mm, 3 mm, 40° upzerlegbar, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 3 mm, 40° updetachable, with thin footplate and Ejector
40-014-24	Kerrison Stanze, 230 mm, 4 mm, 40° up	Kerrison Punch, 230 mm, 4 mm, 40° up
40-014-24 B	Kerrison Stanze, 230 mm, 4 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 4 mm, 40° upwith ceramic coating
40-014-24 BE	Kerrison Stanze, 230 mm, 4 mm, 40° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 230 mm, 4 mm, 40° upwith ceramic coating and Ejector
40-014-24 BF	Kerrison Stanze, 230 mm, 4 mm, 40° upmit Keramikbeschichtung und dünner Fußplatte	Kerrison Punch, 230 mm, 4 mm, 40° upwith ceramic coating and thin footplate
40-014-24 BFE	Kerrison Stanze, 230 mm, 4 mm, 40° upmit Keramikbeschichtung und dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 4 mm, 40° upwith ceramic coating and thin footplate and Ejector
40-014-24 E	Kerrison Stanze, 230 mm, 4 mm, 40° upmit Auswerfer	Kerrison Punch, 230 mm, 4 mm, 40° upwith Ejector
40-014-24 F	Kerrison Stanze, 230 mm, 4 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 4 mm, 40° upwith thin footplate
40-014-24 FE	Kerrison Stanze, 230 mm, 4 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 4 mm, 40° upwith thin footplate and Ejector
40-014-24 Z	Kerrison Stanze, 230 mm, 4 mm, 40° upzerlegbar	Kerrison Punch, 230 mm, 4 mm, 40° updetachable
40-014-24 ZB	Kerrison Stanze, 230 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 230 mm, 4 mm, 40° updetachable, with ceramic coating
40-014-24 ZBE	Kerrison Stanze, 230 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung und Auswerfer	Kerrison Punch, 230 mm, 4 mm, 40° updetachable, with ceramic coating and Ejector
40-014-24 ZBF	Kerrison Stanze, 230 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung und dünner Fußplatte	Kerrison Punch, 230 mm, 4 mm, 40° updetachable, with ceramic coating and thin footplate
40-014-24 ZBFE	Kerrison Stanze, 230 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 4 mm, 40° updetachable, with ceramic coating thin footplate and Ejector
40-014-24 ZE	Kerrison Stanze, 230 mm, 4 mm, 40° upzerlegbar, mit Auswerfer	Kerrison Punch, 230 mm, 4 mm, 40° updetachable, with Ejector
40-014-24 ZF	Kerrison Stanze, 230 mm, 4 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 230 mm, 4 mm, 40° updetachable, with thin footplate
40-014-24 ZFE	Kerrison Stanze, 230 mm, 4 mm, 40° upzerlegbar, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 4 mm, 40° updetachable, with thin footplate and Ejector
40-014-25	Kerrison Stanze, 230 mm, 5 mm, 40° up	Kerrison Punch, 230 mm, 5 mm, 40° up
40-014-25 B	Kerrison Stanze, 230 mm, 5 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 5 mm, 40° upwith ceramic coating
40-014-25 E	Kerrison Stanze, 230 mm, 5 mm, 40° upmit Auswerfer	Kerrison Punch, 230 mm, 5 mm, 40° upwith Ejector
40-014-25 F	Kerrison Stanze, 230 mm, 5 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 5 mm, 40° upwith thin footplate



40-014-25 FE	Kerrison Stanze, 230 mm, 5 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 5 mm, 40° upwith thin footplate and Ejector
40-014-25 Z	Kerrison Stanze, 230 mm, 5 mm, 40° upzerlegbar	Kerrison Punch, 230 mm, 5 mm, 40° updetachable
40-014-25 ZB	Kerrison Stanze, 230 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 230 mm, 5 mm, 40° updetachable, with ceramic coating
40-014-25 ZBE	Kerrison Stanze, 230 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtungund Auswerfer	Kerrison Punch, 230 mm, 5 mm, 40° updetachable, with ceramic coating andEjector
40-014-25 ZBF	Kerrison Stanze, 230 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 230 mm, 5 mm, 40° updetachable, with ceramic coatingand thin footplate
40-014-25 ZBFE	Kerrison Stanze, 230 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtungdünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 5 mm, 40° updetachable, with ceramic coatingthin footplate and Ejector
40-014-25 ZE	Kerrison Stanze, 230 mm, 5 mm, 40° upzerlegbar, mit Auswerfer	Kerrison Punch, 230 mm, 5 mm, 40° updetachable, with Ejector
40-014-25 ZF	Kerrison Stanze, 230 mm, 5 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 230 mm, 5 mm, 40° updetachable, with thin footplate
40-014-25 ZFE	Kerrison Stanze, 230 mm, 5 mm, 40° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 230 mm, 5 mm, 40° updetachable, with thin footplate andEjector
40-014-26	Kerrison Stanze, 230 mm, 6 mm, 40° up	Kerrison Punch, 230 mm, 6 mm, 40° up
40-014-26 B	Kerrison Stanze, 230 mm, 6 mm, 40° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 6 mm, 40° upwith ceramic coating
40-014-26 BF	Kerrison Stanze, 230 mm, 6 mm, 40° upmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 230 mm, 6 mm, 40° upwith ceramic coating and thin footplate
40-014-26 F	Kerrison Stanze, 230 mm, 6 mm, 40° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 6 mm, 40° upwith thin footplate
40-014-26 Z	Kerrison Stanze, 230 mm, 6 mm, 40° upzerlegbar	Kerrison Punch, 230 mm, 6 mm, 40° updetachable
40-014-26 ZB	Kerrison Stanze, 230 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 230 mm, 6 mm, 40° updetachable, with ceramic coating
40-014-26 ZBE	Kerrison Stanze, 230 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtungund Auswerfer	Kerrison Punch, 230 mm, 6 mm, 40° updetachable, with ceramic coating andEjector
40-014-26 ZBF	Kerrison Stanze, 230 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 230 mm, 6 mm, 40° updetachable, with ceramic coatingand thin footplate
40-014-26 ZBFE	Kerrison Stanze, 230 mm, 6 mm, 40° upzerlegbar, mit Keramikbeschichtungdünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 6 mm, 40° updetachable, with ceramic coatingthin footplate and Ejector
40-014-26 ZE	Kerrison Stanze, 230 mm, 6 mm, 40° upzerlegbar, mit Auswerfer	Kerrison Punch, 230 mm, 6 mm, 40° updetachable, with Ejector
40-014-26 ZF	Kerrison Stanze, 230 mm, 6 mm, 40° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 230 mm, 6 mm, 40° updetachable, with thin footplate
40-014-26 ZFE	Kerrison Stanze, 230 mm, 6 mm, 40° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 230 mm, 6 mm, 40° updetachable, with thin footplate andEjector
40-014-33	Kerrison Stanze, 300 mm, 3 mm, 40° upSonderlänge	Kerrison Punch, 300 mm, 3 mm, 40° upspecial length
40-014-33 BE	Kerrison Stanze, 300 mm, 3 mm, 40° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 300 mm, 3 mm, 40° upwith ceramic coating and Ejector
40-014-33 E	Kerrison Stanze, 300 mm, 3 mm, 40° upmit Auswerfer	Kerrison Punch, 300 mm, 3 mm, 40° upwith Ejector
40-014-34	Kerrison Stanze, 300 mm, 4 mm, 40° upSonderlänge	Kerrison Punch, 300 mm, 4 mm, 40° upspecial length
40-014-34 BE	Kerrison Stanze, 300 mm, 4 mm, 40° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 300 mm, 4 mm, 40° upwith ceramic coating and Ejector
40-014-34 E	Kerrison Stanze, 300 mm, 4 mm, 40° upmit Auswerfer	Kerrison Punch, 300 mm, 4 mm, 40° upwith Ejector
40-014-34 FE	Kerrison Stanze, 300 mm, 4 mm, 40° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 300 mm, 4 mm, 40° upwith thin footplate and Ejector
40-014-35	Kerrison Stanze, 300 mm, 5 mm, 40° upSonderlänge	Kerrison Punch, 300 mm, 5 mm, 40° upspecial length
40-014-35 BE	Kerrison Stanze, 300 mm, 5 mm, 40° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 300 mm, 5 mm, 40° upwith ceramic coating and Ejector
40-014-35 E	Kerrison Stanze, 300 mm, 5 mm, 40° upmit Auswerfer	Kerrison Punch, 300 mm, 5 mm, 40° upwith Ejector
40-014-36	Kerrison Stanze, 300 mm, 6 mm, 40° upSonderlänge	Kerrison Punch, 300 mm, 6 mm, 40° upspecial length
40-015-12 ZBF	Kerrison Stanze, 200 mm, 2 mm, 40° upzerlegbar, mit Keramikbeschichtung,mit dünner Fußplatte, Öffnung 15 mm	Kerrison Punch, 200 mm, 2 mm, 40° updetachable, with ceramic coating,with thin footplate, opening 15 mm
40-015-12 ZF	Kerrison Stanze, 200 mm, 2 mm, 40° upzerlegbar, mit dünner Fußplatte,Öffnung 15 mm	Kerrison Punch, 200 mm, 2 mm, 40° updetachable, with thin footplate,opening 15 mm
40-015-13 ZBF	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung,mit dünner Fußplatte, Öffnung 15 mm	Kerrison Punch, 200 mm, 3 mm, 40° updetachable, with ceramic coating,with thin footplate, opening 15 mm
40-015-13 ZF	Kerrison Stanze, 200 mm, 3 mm, 40° upzerlegbar, mit dünner Fußplatte,Öffnung 15 mm	Kerrison Punch, 200 mm, 3 mm, 40° updetachable, with thin footplate,opening 15 mm
40-015-14 ZBF	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar, mit Keramikbeschichtung,mit dünner Fußplatte, Öffnung 15 mm	Kerrison Punch, 200 mm, 4 mm, 40° updetachable, with ceramic coating,with thin footplate, opening 15 mm
40-015-14 ZF	Kerrison Stanze, 200 mm, 4 mm, 40° upzerlegbar, mit dünner Fußplatte,Öffnung 15 mm	Kerrison Punch, 200 mm, 4 mm, 40° updetachable, with thin footplate,opening 15 mm

40-015-15 ZBF	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte, Öffnung 15 mm	Kerrison Punch, 200 mm, 5 mm, 40° updetachable, with ceramic coating, with thin footplate, opening 15 mm
40-015-15 ZF	Kerrison Stanze, 200 mm, 5 mm, 40° upzerlegbar, mit dünner Fußplatte, Öffnung 15 mm	Kerrison Punch, 200 mm, 5 mm, 40° updetachable, with thin footplate, opening 15 mm
40-016-01	Kerrison Stanze, 180 mm, 1 mm, 90° up	Kerrison Punch, 180 mm, 1 mm, 90° up
40-016-01 B	Kerrison Stanze, 180 mm, 1 mm, 90° up mit Keramikbeschichtung	Kerrison Punch, 180 mm, 1 mm, 90° up with ceramic coating
40-016-01 BF	Kerrison Stanze, 180 mm, 1 mm, 90° up mit Keramikbeschichtung und dünner Fußplatte	Kerrison Punch, 180 mm, 1 mm, 90° up with ceramic coating and thin footplate
40-016-01 F	Kerrison Stanze, 180 mm, 1 mm, 90° up mit dünner Fußplatte	Kerrison Punch, 180 mm, 1 mm, 90° up with thin footplate
40-016-01 Z	Kerrison Stanze, 180 mm, 1 mm, 90° upzerlegbar	Kerrison Punch, 180 mm, 1 mm, 90° updetachable
40-016-01 ZB	Kerrison Stanze, 180 mm, 1 mm, 90° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 180 mm, 1 mm, 90° updetachable, with ceramic coating
40-016-01 ZBF	Kerrison Stanze, 180 mm, 1 mm, 90° upzerlegbar, mit Keramikbeschichtung, mit dünner Fußplatte	Kerrison Punch, 180 mm, 1 mm, 90° updetachable, with ceramic coating, with thin footplate
40-016-01 ZF	Kerrison Stanze, 180 mm, 1 mm, 90° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 180 mm, 1 mm, 90° updetachable, with thin footplate
40-016-02	Kerrison Stanze, 180 mm, 2 mm, 90° up	Kerrison Punch, 180 mm, 2 mm, 90° up
40-016-02 B	Kerrison Stanze, 180 mm, 2 mm, 90° up mit Keramikbeschichtung	Kerrison Punch, 180 mm, 2 mm, 90° up with ceramic coating
40-016-02 BF	Kerrison Stanze, 180 mm, 2 mm, 90° up mit Keramikbeschichtung und dünner Fußplatte	Kerrison Punch, 180 mm, 2 mm, 90° up with ceramic coating and thin footplate
40-016-02 F	Kerrison Stanze, 180 mm, 2 mm, 90° up mit dünner Fußplatte	Kerrison Punch, 180 mm, 2 mm, 90° up with thin footplate
40-016-02 ZBE	Kerrison Stanze, 180 mm, 2 mm, 90° upzerlegbar, mit Keramikbeschichtung und Auswerfer	Kerrison Punch, 180 mm, 2 mm, 90° updetachable, with ceramic coating and Ejector
40-016-02 ZE	Kerrison Stanze, 180 mm, 2 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 2 mm, 90° updetachable, with Ejector
40-016-02 ZFE	Kerrison Stanze, 180 mm, 2 mm, 90° upzerlegbar, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 2 mm, 90° updetachable, with thin footplate and Ejector
40-016-03	Kerrison Stanze, 180 mm, 3 mm, 90° up	Kerrison Punch, 180 mm, 3 mm, 90° up
40-016-03 B	Kerrison Stanze, 180 mm, 3 mm, 90° up mit Keramikbeschichtung	Kerrison Punch, 180 mm, 3 mm, 90° up with ceramic coating
40-016-03 E	Kerrison Stanze, 180 mm, 3 mm, 90° up mit Auswerfer	Kerrison Punch, 180 mm, 3 mm, 90° up with Ejector
40-016-03 F	Kerrison Stanze, 180 mm, 3 mm, 90° up mit dünner Fußplatte	Kerrison Punch, 180 mm, 3 mm, 90° up with thin footplate
40-016-03 FE	Kerrison Stanze, 180 mm, 3 mm, 90° up mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 90° up with thin footplate and Ejector
40-016-03 ZBE	Kerrison Stanze, 180 mm, 3 mm, 90° upzerlegbar, mit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 90° updetachable, with ceramic coating, and Ejector
40-016-03 ZBFE	Kerrison Stanze, 180 mm, 3 mm, 90° upzerlegbar, mit Keramikbeschichtung, dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 90° updetachable, with ceramic coating, thin footplate and Ejector
40-016-03 ZE	Kerrison Stanze, 180 mm, 3 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 3 mm, 90° updetachable, with Ejector
40-016-03 ZFE	Kerrison Stanze, 180 mm, 3 mm, 90° upzerlegbar, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 90° updetachable, with thin footplate and Ejector
40-016-04	Kerrison Stanze, 180 mm, 4 mm, 90° up	Kerrison Punch, 180 mm, 4 mm, 90° up
40-016-04 B	Kerrison Stanze, 180 mm, 4 mm, 90° up mit Keramikbeschichtung	Kerrison Punch, 180 mm, 4 mm, 90° up with ceramic coating
40-016-04 F	Kerrison Stanze, 180 mm, 4 mm, 90° up mit dünner Fußplatte	Kerrison Punch, 180 mm, 4 mm, 90° up with thin footplate
40-016-04 ZBE	Kerrison Stanze, 180 mm, 4 mm, 90° upzerlegbar, mit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 90° updetachable, with ceramic coating, and Ejector
40-016-04 ZBFE	Kerrison Stanze, 180 mm, 4 mm, 90° upzerlegbar, mit Keramikbeschichtung, dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 90° updetachable, with ceramic coating, thin footplate and Ejector
40-016-04 ZE	Kerrison Stanze, 180 mm, 4 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 4 mm, 90° updetachable, with Ejector
40-016-04 ZFE	Kerrison Stanze, 180 mm, 4 mm, 90° upzerlegbar, mit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 90° updetachable, with thin footplate and Ejector
40-016-05	Kerrison Stanze, 180 mm, 5 mm, 90° up	Kerrison Punch, 180 mm, 5 mm, 90° up
40-016-05 E	Kerrison Stanze, 180 mm, 5 mm, 90° up mit Auswerfer	Kerrison Punch, 180 mm, 5 mm, 90° up with Ejector
40-016-05 F	Kerrison Stanze, 180 mm, 5 mm, 90° up mit dünner Fußplatte	Kerrison Punch, 180 mm, 5 mm, 90° up with thin footplate
40-016-05 ZBE	Kerrison Stanze, 180 mm, 5 mm, 90° upzerlegbar, mit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 180 mm, 5 mm, 90° updetachable, with ceramic coating, and Ejector

40-016-05 ZE	Kerrison Stanze, 180 mm, 5 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 5 mm, 90° updetachable, with Ejector
40-016-06	Kerrison Stanze, 180 mm, 6 mm, 90° up	Kerrison Punch, 180 mm, 6 mm, 90° up
40-016-06 F	Kerrison Stanze, 180 mm, 6 mm, 90° upmit dünner Fußplatte	Kerrison Punch, 180 mm, 6 mm, 90° upwith thin footplate
40-016-06 ZBE	Kerrison Stanze, 180 mm, 6 mm, 90° upzerlegbar, mit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 180 mm, 6 mm, 90° updetachable, with ceramic coating, and Ejector
40-016-06 ZE	Kerrison Stanze, 180 mm, 6 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 180 mm, 6 mm, 90° updetachable, with Ejector
40-016-11	Kerrison Stanze, 200 mm, 1 mm, 90° up	Kerrison Punch, 200 mm, 1 mm, 90° up
40-016-11 F	Kerrison Stanze, 200 mm, 1 mm, 90° upmit dünner Fußplatte	Kerrison Punch, 200 mm, 1 mm, 90° upwith thin footplate
40-016-11 Z	Kerrison Stanze, 200 mm, 1 mm, 90° upzerlegbar	Kerrison Punch, 200 mm, 1 mm, 90° updetachable
40-016-11 ZF	Kerrison Stanze, 200 mm, 1 mm, 90° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 200 mm, 1 mm, 90° updetachable, with thin footplate
40-016-12	Kerrison Stanze, 200 mm, 2 mm, 90° up	Kerrison Punch, 200 mm, 2 mm, 90° up
40-016-12 BE	Kerrison Stanze, 200 mm, 2 mm, 90° upmit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 200 mm, 2 mm, 90° upwith ceramic coating, and Ejector
40-016-12 BF	Kerrison Stanze, 200 mm, 2 mm, 90° upmit Keramikbeschichtung, und dünnerFußplatte	Kerrison Punch, 200 mm, 2 mm, 90° upwith ceramic coating, and thin footplate
40-016-12 E	Kerrison Stanze, 200 mm, 2 mm, 90° upmit Auswerfer	Kerrison Punch, 200 mm, 2 mm, 90° upwith Ejector
40-016-12 F	Kerrison Stanze, 200 mm, 2 mm, 90° upmit dünner Fußplatte	Kerrison Punch, 200 mm, 2 mm, 90° upwith thin footplate
40-016-12 FE	Kerrison Stanze, 200 mm, 2 mm, 90° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 2 mm, 90° upwith thin footplate and Ejector
40-016-12 ZE	Kerrison Stanze, 200 mm, 2 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 200 mm, 2 mm, 90° updetachable, with Ejector
40-016-12 ZFE	Kerrison Stanze, 200 mm, 2 mm, 90° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 200 mm, 2 mm, 90° updetachable, with thin footplate andEjector
40-016-13	Kerrison Stanze, 200 mm, 3 mm, 90° up	Kerrison Punch, 200 mm, 3 mm, 90° up
40-016-13 BE	Kerrison Stanze, 200 mm, 3 mm, 90° upmit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 90° upwith ceramic coating, and Ejector
40-016-13 BF	Kerrison Stanze, 200 mm, 3 mm, 90° upmit Keramikbeschichtung, und dünnerFußplatte	Kerrison Punch, 200 mm, 3 mm, 90° upwith ceramic coating, and thin footplate
40-016-13 E	Kerrison Stanze, 200 mm, 3 mm, 90° upmit Auswerfer	Kerrison Punch, 200 mm, 3 mm, 90° upwith Ejector
40-016-13 F	Kerrison Stanze, 200 mm, 3 mm, 90° upmit dünner Fußplatte	Kerrison Punch, 200 mm, 3 mm, 90° upwith thin footplate
40-016-13 FE	Kerrison Stanze, 200 mm, 3 mm, 90° upmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 90° upwith thin footplate and Ejector
40-016-13 ZBE	Kerrison Stanze, 200 mm, 3 mm, 90° upzerlegbar, mit Keramikbeschichtungund Auswerfer	Kerrison Punch, 200 mm, 3 mm, 90° updetachable, with ceramic coatingand Ejector
40-016-13 ZE	Kerrison Stanze, 200 mm, 3 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 200 mm, 3 mm, 90° updetachable, with Ejector
40-016-13 ZFE	Kerrison Stanze, 200 mm, 3 mm, 90° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 200 mm, 3 mm, 90° updetachable, with thin footplate andEjector
40-016-14	Kerrison Stanze, 200 mm, 4 mm, 90° up	Kerrison Punch, 200 mm, 4 mm, 90° up
40-016-14 BE	Kerrison Stanze, 200 mm, 4 mm, 90° upmit Keramikbeschichtung, und Auswerfer	Kerrison Punch, 200 mm, 4 mm, 90° upwith ceramic coating, and Ejector
40-016-14 ZE	Kerrison Stanze, 200 mm, 4 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 200 mm, 4 mm, 90° updetachable, with Ejector
40-016-15	Kerrison Stanze, 200 mm, 5 mm, 90° up	Kerrison Punch, 200 mm, 5 mm, 90° up
40-016-15 ZBE	Kerrison Stanze, 200 mm, 5 mm, 90° upzerlegbar, mit Keramikbeschichtung	Kerrison Punch, 200 mm, 5 mm, 90° updetachable, with ceramic coating
40-016-15 ZE	Kerrison Stanze, 200 mm, 5 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 200 mm, 5 mm, 90° updetachable, with Ejector
40-016-16	Kerrison Stanze, 200 mm, 6 mm, 90° up	Kerrison Punch, 200 mm, 6 mm, 90° up
40-016-16 ZE	Kerrison Stanze, 200 mm, 6 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 200 mm, 6 mm, 90° updetachable, with Ejector
40-016-21	Kerrison Stanze, 230 mm, 1 mm, 90° up	Kerrison Punch, 230 mm, 1 mm, 90° up
40-016-21 B	Kerrison Stanze, 230 mm, 1 mm, 90° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 1 mm, 90° upwith ceramic coating
40-016-21 F	Kerrison Stanze, 230 mm, 1 mm, 90° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 1 mm, 90° upwith thin footplate
40-016-21 Z	Kerrison Stanze, 230 mm, 1 mm, 90° upzerlegbar	Kerrison Punch, 230 mm, 1 mm, 90° updetachable
40-016-21 ZF	Kerrison Stanze, 230 mm, 1 mm, 90° upzerlegbar, mit dünner Fußplatte	Kerrison Punch, 230 mm, 1 mm, 90° updetachable, with thin footplate
40-016-22	Kerrison Stanze, 230 mm, 2 mm, 90° up	Kerrison Punch, 230 mm, 2 mm, 90° up

40-016-22 B	Kerrison Stanze, 230 mm, 2 mm, 90° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 2 mm, 90° upwith ceramic coating
40-016-22 F	Kerrison Stanze, 230 mm, 2 mm, 90° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 2 mm, 90° upwith thin footplate
40-016-22 ZE	Kerrison Stanze, 230 mm, 2 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 230 mm, 2 mm, 90° updetachable, with Ejector
40-016-22 ZFE	Kerrison Stanze, 230 mm, 2 mm, 90° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 230 mm, 2 mm, 90° updetachable, with thin footplate andEjector
40-016-23	Kerrison Stanze, 230 mm, 3 mm, 90° up	Kerrison Punch, 230 mm, 3 mm, 90° up
40-016-23 B	Kerrison Stanze, 230 mm, 3 mm, 90° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 3 mm, 90° upwith ceramic coating
40-016-23 BE	Kerrison Stanze, 230 mm, 3 mm, 90° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 230 mm, 3 mm, 90° upwith ceramic coating and Ejector
40-016-23 E	Kerrison Stanze, 230 mm, 3 mm, 90° upmit Auswerfer	Kerrison Punch, 230 mm, 3 mm, 90° upwith Ejector
40-016-23 F	Kerrison Stanze, 230 mm, 3 mm, 90° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 3 mm, 90° upwith thin footplate
40-016-23 ZE	Kerrison Stanze, 230 mm, 3 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 230 mm, 3 mm, 90° updetachable, with Ejector
40-016-23 ZFE	Kerrison Stanze, 230 mm, 3 mm, 90° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 230 mm, 3 mm, 90° updetachable, with thin footplate andEjector
40-016-24	Kerrison Stanze, 230 mm, 4 mm, 90° up	Kerrison Punch, 230 mm, 4 mm, 90° up
40-016-24 B	Kerrison Stanze, 230 mm, 4 mm, 90° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 4 mm, 90° upwith ceramic coating
40-016-24 BE	Kerrison Stanze, 230 mm, 4 mm, 90° upmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 230 mm, 4 mm, 90° upwith ceramic coating and Ejector
40-016-24 F	Kerrison Stanze, 230 mm, 4 mm, 90° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 4 mm, 90° upwith thin footplate
40-016-24 ZE	Kerrison Stanze, 230 mm, 4 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 230 mm, 4 mm, 90° updetachable, with Ejector
40-016-24 ZFE	Kerrison Stanze, 230 mm, 4 mm, 90° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 230 mm, 4 mm, 90° updetachable, with thin footplate andEjector
40-016-25	Kerrison Stanze, 230 mm, 5 mm, 90° up	Kerrison Punch, 230 mm, 5 mm, 90° up
40-016-25 B	Kerrison Stanze, 230 mm, 5 mm, 90° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 5 mm, 90° upwith ceramic coating
40-016-25 E	Kerrison Stanze, 230 mm, 5 mm, 90° upmit Auswerfer	Kerrison Punch, 230 mm, 5 mm, 90° upwith Ejector
40-016-25 F	Kerrison Stanze, 230 mm, 5 mm, 90° upmit dünner Fußplatte	Kerrison Punch, 230 mm, 5 mm, 90° upwith thin footplate
40-016-25 ZE	Kerrison Stanze, 230 mm, 5 mm, 90° upzerlegbar, mit Auswerfer	Kerrison Punch, 230 mm, 5 mm, 90° updetachable, with Ejector
40-016-25 ZFE	Kerrison Stanze, 230 mm, 5 mm, 90° upzerlegbar, mit dünner Fußplatte undAuswerfer	Kerrison Punch, 230 mm, 5 mm, 90° updetachable, with thin footplate andEjector
40-016-26	Kerrison Stanze, 230 mm, 6 mm, 90° up	Kerrison Punch, 230 mm, 6 mm, 90° up
40-016-26 B	Kerrison Stanze, 230 mm, 6 mm, 90° upmit Keramikbeschichtung	Kerrison Punch, 230 mm, 6 mm, 90° upwith ceramic coating
40-017-01	Kerrison Stanze, 180 mm, 1 mm, 40° down	Kerrison Punch, 180 mm, 1 mm, 40° down
40-017-01 B	Kerrison Stanze, 180 mm, 1 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 1 mm, 40° downwith ceramic coating
40-017-01 BF	Kerrison Stanze, 180 mm, 1 mm, 40° downmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 180 mm, 1 mm, 40° downwith ceramic coating and thin footplate
40-017-01 F	Kerrison Stanze, 180 mm, 1 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 1 mm, 40° downwith thin footplate
40-017-02	Kerrison Stanze, 180 mm, 2 mm, 40° down	Kerrison Punch, 180 mm, 2 mm, 40° down
40-017-02 B	Kerrison Stanze, 180 mm, 2 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 2 mm, 40° downwith ceramic coating
40-017-02 F	Kerrison Stanze, 180 mm, 2 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 2 mm, 40° downwith thin footplate
40-017-02 FE	Kerrison Stanze, 180 mm, 2 mm, 40° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 2 mm, 40° downwith thin footplate and Ejector
40-017-03	Kerrison Stanze, 180 mm, 3 mm, 40° down	Kerrison Punch, 180 mm, 3 mm, 40° down
40-017-03 B	Kerrison Stanze, 180 mm, 3 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 3 mm, 40° downwith ceramic coating
40-017-03 F	Kerrison Stanze, 180 mm, 3 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 3 mm, 40° downwith thin footplate
40-017-03 FE	Kerrison Stanze, 180 mm, 3 mm, 40° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 40° downwith thin footplate and Ejector
40-017-04	Kerrison Stanze, 180 mm, 4 mm, 40° down	Kerrison Punch, 180 mm, 4 mm, 40° down
40-017-04 B	Kerrison Stanze, 180 mm, 4 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 4 mm, 40° downwith ceramic coating

40-017-04 F	Kerrison Stanze, 180 mm, 4 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 4 mm, 40° downwith thin footplate
40-017-04 FE	Kerrison Stanze, 180 mm, 4 mm, 40° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 40° downwith thin footplate and Ejector
40-017-05	Kerrison Stanze, 180 mm, 5 mm, 40° down	Kerrison Punch, 180 mm, 5 mm, 40° down
40-017-05 B	Kerrison Stanze, 180 mm, 5 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 5 mm, 40° downwith ceramic coating
40-017-05 F	Kerrison Stanze, 180 mm, 5 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 5 mm, 40° downwith thin footplate
40-017-06	Kerrison Stanze, 180 mm, 6 mm, 40° down	Kerrison Punch, 180 mm, 6 mm, 40° down
40-017-06 B	Kerrison Stanze, 180 mm, 6 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 6 mm, 40° downwith ceramic coating
40-017-06 F	Kerrison Stanze, 180 mm, 6 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 6 mm, 40° downwith thin footplate
40-017-11	Kerrison Stanze, 200 mm, 1 mm, 40° down	Kerrison Punch, 200 mm, 1 mm, 40° down
40-017-11 B	Kerrison Stanze, 200 mm, 1 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 1 mm, 40° downwith ceramic coating
40-017-11 F	Kerrison Stanze, 200 mm, 1 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 200 mm, 1 mm, 40° downwith thin footplate
40-017-12	Kerrison Stanze, 200 mm, 2 mm, 40° down	Kerrison Punch, 200 mm, 2 mm, 40° down
40-017-12 B	Kerrison Stanze, 200 mm, 2 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 2 mm, 40° downwith ceramic coating
40-017-12 BF	Kerrison Stanze, 200 mm, 2 mm, 40° downmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 200 mm, 2 mm, 40° downwith ceramic coating and thin footplate
40-017-12 F	Kerrison Stanze, 200 mm, 2 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 200 mm, 2 mm, 40° downwith thin footplate
40-017-13	Kerrison Stanze, 200 mm, 3 mm, 40° down	Kerrison Punch, 200 mm, 3 mm, 40° down
40-017-13 B	Kerrison Stanze, 200 mm, 3 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 3 mm, 40° downwith ceramic coating
40-017-13 BE	Kerrison Stanze, 200 mm, 3 mm, 40° downmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° downwith ceramic coating and Ejector
40-017-13 BF	Kerrison Stanze, 200 mm, 3 mm, 40° downmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 200 mm, 3 mm, 40° downwith ceramic coating and thin footplate
40-017-13 BFE	Kerrison Stanze, 200 mm, 3 mm, 40° downmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° downwith ceramic coating, thin footplate andEjector
40-017-13 FE	Kerrison Stanze, 200 mm, 3 mm, 40° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 40° downwith thin footplate and Ejector
40-017-14	Kerrison Stanze, 200 mm, 4 mm, 40° down	Kerrison Punch, 200 mm, 4 mm, 40° down
40-017-14 B	Kerrison Stanze, 200 mm, 4 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 4 mm, 40° downwith ceramic coating
40-017-14 BE	Kerrison Stanze, 200 mm, 4 mm, 40° downmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 200 mm, 4 mm, 40° downwith ceramic coating and Ejector
40-017-14 FE	Kerrison Stanze, 200 mm, 4 mm, 40° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 4 mm, 40° downwith thin footplate and Ejector
40-017-15	Kerrison Stanze, 200 mm, 5 mm, 40° down	Kerrison Punch, 200 mm, 5 mm, 40° down
40-017-15 B	Kerrison Stanze, 200 mm, 5 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 5 mm, 40° downwith ceramic coating
40-017-15 FE	Kerrison Stanze, 200 mm, 5 mm, 40° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 5 mm, 40° downwith thin footplate and Ejector
40-017-16	Kerrison Stanze, 200 mm, 6 mm, 40° down	Kerrison Punch, 200 mm, 6 mm, 40° down
40-017-16 B	Kerrison Stanze, 200 mm, 6 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 6 mm, 40° downwith ceramic coating
40-017-16 FE	Kerrison Stanze, 200 mm, 6 mm, 40° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 6 mm, 40° downwith thin footplate and Ejector
40-017-21	Kerrison Stanze, 230 mm, 1 mm, 40° down	Kerrison Punch, 230 mm, 1 mm, 40° down
40-017-21 B	Kerrison Stanze, 230 mm, 1 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 1 mm, 40° downwith ceramic coating
40-017-21 F	Kerrison Stanze, 230 mm, 1 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 1 mm, 40° downwith thin footplate
40-017-22	Kerrison Stanze, 230 mm, 2 mm, 40° down	Kerrison Punch, 230 mm, 2 mm, 40° down
40-017-22 B	Kerrison Stanze, 230 mm, 2 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 2 mm, 40° downwith ceramic coating
40-017-22 F	Kerrison Stanze, 230 mm, 2 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 2 mm, 40° downwith thin footplate
40-017-23	Kerrison Stanze, 230 mm, 3 mm, 40° down	Kerrison Punch, 230 mm, 3 mm, 40° down
40-017-23 B	Kerrison Stanze, 230 mm, 3 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 3 mm, 40° downwith ceramic coating

40-017-23 E	Kerrison Stanze, 230 mm, 3 mm, 40° downmit Auswerfer	Kerrison Punch, 230 mm, 3 mm, 40° downwith Ejector
40-017-23 F	Kerrison Stanze, 230 mm, 3 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 3 mm, 40° downwith thin footplate
40-017-24	Kerrison Stanze, 230 mm, 4 mm, 40° down	Kerrison Punch, 230 mm, 4 mm, 40° down
40-017-24 B	Kerrison Stanze, 230 mm, 4 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 4 mm, 40° downwith ceramic coating
40-017-24 E	Kerrison Stanze, 230 mm, 4 mm, 40° downmit Auswerfer	Kerrison Punch, 230 mm, 4 mm, 40° downwith Ejector
40-017-24 F	Kerrison Stanze, 230 mm, 4 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 4 mm, 40° downwith thin footplate
40-017-25	Kerrison Stanze, 230 mm, 5 mm, 40° down	Kerrison Punch, 230 mm, 5 mm, 40° down
40-017-25 B	Kerrison Stanze, 230 mm, 5 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 5 mm, 40° downwith ceramic coating
40-017-25 E	Kerrison Stanze, 230 mm, 5 mm, 40° downmit Auswerfer	Kerrison Punch, 230 mm, 5 mm, 40° downwith Ejector
40-017-25 F	Kerrison Stanze, 230 mm, 5 mm, 40° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 5 mm, 40° downwith thin footplate
40-017-26	Kerrison Stanze, 230 mm, 6 mm, 40° down	Kerrison Punch, 230 mm, 6 mm, 40° down
40-017-26 B	Kerrison Stanze, 230 mm, 6 mm, 40° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 6 mm, 40° downwith ceramic coating
40-019-01	Kerrison Stanze, 180 mm, 1 mm, 90° down	Kerrison Punch, 180 mm, 1 mm, 90° down
40-019-01 B	Kerrison Stanze, 180 mm, 1 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 1 mm, 90° downwith ceramic coating
40-019-01 BF	Kerrison Stanze, 180 mm, 1 mm, 90° downmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 180 mm, 1 mm, 90° downwith ceramic coating and thin footplate
40-019-01 F	Kerrison Stanze, 180 mm, 1 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 1 mm, 90° downwith thin footplate
40-019-02	Kerrison Stanze, 180 mm, 2 mm, 90° down	Kerrison Punch, 180 mm, 2 mm, 90° down
40-019-02 B	Kerrison Stanze, 180 mm, 2 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 2 mm, 90° downwith ceramic coating
40-019-02 BF	Kerrison Stanze, 180 mm, 2 mm, 90° downmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 180 mm, 2 mm, 90° downwith ceramic coating and thin footplate
40-019-02 F	Kerrison Stanze, 180 mm, 2 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 2 mm, 90° downwith thin footplate
40-019-03	Kerrison Stanze, 180 mm, 3 mm, 90° down	Kerrison Punch, 180 mm, 3 mm, 90° down
40-019-03 B	Kerrison Stanze, 180 mm, 3 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 3 mm, 90° downwith ceramic coating
40-019-03 BE	Kerrison Stanze, 180 mm, 3 mm, 90° downmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 90° downwith ceramic coating and Ejector
40-019-03 F	Kerrison Stanze, 180 mm, 3 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 3 mm, 90° downwith thin footplate
40-019-03 FE	Kerrison Stanze, 180 mm, 3 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 3 mm, 90° downwith thin footplate and Ejector
40-019-04	Kerrison Stanze, 180 mm, 4 mm, 90° down	Kerrison Punch, 180 mm, 4 mm, 90° down
40-019-04 B	Kerrison Stanze, 180 mm, 4 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 4 mm, 90° downwith ceramic coating
40-019-04 BE	Kerrison Stanze, 180 mm, 4 mm, 90° downmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 180 mm, 4 mm, 90° downwith ceramic coating and Ejector
40-019-05	Kerrison Stanze, 180 mm, 5 mm, 90° down	Kerrison Punch, 180 mm, 5 mm, 90° down
40-019-05 B	Kerrison Stanze, 180 mm, 5 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 5 mm, 90° downwith ceramic coating
40-019-05 BE	Kerrison Stanze, 180 mm, 5 mm, 90° downmit Keramikbeschichtung und Auswerfer	Kerrison Punch, 180 mm, 5 mm, 90° downwith ceramic coating and Ejector
40-019-05 E	Kerrison Stanze, 180 mm, 5 mm, 90° downmit Auswerfer	Kerrison Punch, 180 mm, 5 mm, 90° downwith Ejector
40-019-05 FE	Kerrison Stanze, 180 mm, 5 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 180 mm, 5 mm, 90° downwith thin footplate and Ejector
40-019-06	Kerrison Stanze, 180 mm, 6 mm, 90° down	Kerrison Punch, 180 mm, 6 mm, 90° down
40-019-06 B	Kerrison Stanze, 180 mm, 6 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 180 mm, 6 mm, 90° downwith ceramic coating
40-019-06 F	Kerrison Stanze, 180 mm, 6 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 180 mm, 6 mm, 90° downwith thin footplate
40-019-11	Kerrison Stanze, 200 mm, 1 mm, 90° down	Kerrison Punch, 200 mm, 1 mm, 90° down
40-019-11 B	Kerrison Stanze, 200 mm, 1 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 1 mm, 90° downwith ceramic coating
40-019-11 F	Kerrison Stanze, 200 mm, 1 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 200 mm, 1 mm, 90° downwith thin footplate

40-019-12	Kerrison Stanze, 200 mm, 2 mm, 90° down	Kerrison Punch, 200 mm, 2 mm, 90° down
40-019-12 B	Kerrison Stanze, 200 mm, 2 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 2 mm, 90° downwith ceramic coating
40-019-12 BF	Kerrison Stanze, 200 mm, 2 mm, 90° downmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 200 mm, 2 mm, 90° downwith ceramic coating and thin footplate
40-019-12 F	Kerrison Stanze, 200 mm, 2 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 200 mm, 2 mm, 90° downwith thin footplate
40-019-13	Kerrison Stanze, 200 mm, 3 mm, 90° down	Kerrison Punch, 200 mm, 3 mm, 90° down
40-019-13 B	Kerrison Stanze, 200 mm, 3 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 3 mm, 90° downwith ceramic coating
40-019-13 BF	Kerrison Stanze, 200 mm, 3 mm, 90° downmit Keramikbeschichtung und dünnerFußplatte	Kerrison Punch, 200 mm, 3 mm, 90° downwith ceramic coating and thin footplate
40-019-13 BFE	Kerrison Stanze, 200 mm, 3 mm, 90° downmit Keramikbeschichtung, dünner Fuß-platte und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 90° downwith ceramic coating, thin footplate andEjector
40-019-13 F	Kerrison Stanze, 200 mm, 3 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 200 mm, 3 mm, 90° downwith thin footplate
40-019-13 FE	Kerrison Stanze, 200 mm, 3 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 3 mm, 90° downwith thin footplate and Ejector
40-019-14	Kerrison Stanze, 200 mm, 4 mm, 90° down	Kerrison Punch, 200 mm, 4 mm, 90° down
40-019-14 B	Kerrison Stanze, 200 mm, 4 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 4 mm, 90° downwith ceramic coating
40-019-14 F	Kerrison Stanze, 200 mm, 4 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 200 mm, 4 mm, 90° downwith thin footplate
40-019-14 FE	Kerrison Stanze, 200 mm, 4 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 4 mm, 90° downwith thin footplate and Ejector
40-019-15	Kerrison Stanze, 200 mm, 5 mm, 90° down	Kerrison Punch, 200 mm, 5 mm, 90° down
40-019-15 B	Kerrison Stanze, 200 mm, 5 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 5 mm, 90° downwith ceramic coating
40-019-15 F	Kerrison Stanze, 200 mm, 5 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 200 mm, 5 mm, 90° downwith thin footplate
40-019-15 FE	Kerrison Stanze, 200 mm, 5 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 5 mm, 90° downwith thin footplate and Ejector
40-019-16	Kerrison Stanze, 200 mm, 6 mm, 90° down	Kerrison Punch, 200 mm, 6 mm, 90° down
40-019-16 B	Kerrison Stanze, 200 mm, 6 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 200 mm, 6 mm, 90° downwith ceramic coating
40-019-16 FE	Kerrison Stanze, 200 mm, 6 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 200 mm, 6 mm, 90° downwith thin footplate and Ejector
40-019-21	Kerrison Stanze, 230 mm, 1 mm, 90° down	Kerrison Punch, 230 mm, 1 mm, 90° down
40-019-21 B	Kerrison Stanze, 230 mm, 1 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 1 mm, 90° downwith ceramic coating
40-019-21 F	Kerrison Stanze, 230 mm, 1 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 1 mm, 90° downwith thin footplate
40-019-22	Kerrison Stanze, 230 mm, 2 mm, 90° down	Kerrison Punch, 230 mm, 2 mm, 90° down
40-019-22 B	Kerrison Stanze, 230 mm, 2 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 2 mm, 90° downwith ceramic coating
40-019-22 F	Kerrison Stanze, 230 mm, 2 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 2 mm, 90° downwith thin footplate
40-019-23	Kerrison Stanze, 230 mm, 3 mm, 90° down	Kerrison Punch, 230 mm, 3 mm, 90° down
40-019-23 B	Kerrison Stanze, 230 mm, 3 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 3 mm, 90° downwith ceramic coating
40-019-23 E	Kerrison Stanze, 230 mm, 3 mm, 90° downmit Auswerfer	Kerrison Punch, 230 mm, 3 mm, 90° downwith Ejector
40-019-23 F	Kerrison Stanze, 230 mm, 3 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 3 mm, 90° downwith thin footplate
40-019-23 FE	Kerrison Stanze, 230 mm, 3 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 3 mm, 90° downwith thin footplate and Ejector
40-019-24	Kerrison Stanze, 230 mm, 4 mm, 90° down	Kerrison Punch, 230 mm, 4 mm, 90° down
40-019-24 B	Kerrison Stanze, 230 mm, 4 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 4 mm, 90° downwith ceramic coating
40-019-24 F	Kerrison Stanze, 230 mm, 4 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 4 mm, 90° downwith thin footplate
40-019-24 FE	Kerrison Stanze, 230 mm, 4 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 4 mm, 90° downwith thin footplate and Ejector
40-019-25	Kerrison Stanze, 230 mm, 5 mm, 90° down	Kerrison Punch, 230 mm, 5 mm, 90° down
40-019-25 B	Kerrison Stanze, 230 mm, 5 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 5 mm, 90° downwith ceramic coating
40-019-25 F	Kerrison Stanze, 230 mm, 5 mm, 90° downmit dünner Fußplatte	Kerrison Punch, 230 mm, 5 mm, 90° downwith thin footplate

40-019-25 FE	Kerrison Stanze, 230 mm, 5 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 5 mm, 90° downwith thin footplate and Ejector
40-019-26	Kerrison Stanze, 230 mm, 6 mm, 90° down	Kerrison Punch, 230 mm, 6 mm, 90° down
40-019-26 B	Kerrison Stanze, 230 mm, 6 mm, 90° downmit Keramikbeschichtung	Kerrison Punch, 230 mm, 6 mm, 90° downwith ceramic coating
40-019-26 FE	Kerrison Stanze, 230 mm, 6 mm, 90° downmit dünner Fußplatte und Auswerfer	Kerrison Punch, 230 mm, 6 mm, 90° downwith thin footplate and Ejector
40-020-01	Bajonett Kerrison Stanze, 110 mm, 1 mm,40° up	Bayonet Kerrison Punch, 110 mm, 1 mm,40° up
40-020-01 B	Bajonett Kerrison Stanze, 110 mm, 1 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 110 mm, 1 mm,40° up, with ceramic coating
40-020-01 F	Bajonett Kerrison Stanze, 110 mm, 1 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 110 mm, 1 mm,40° up, with thin Footplate
40-020-02	Bajonett Kerrison Stanze, 110 mm, 2 mm,40° up	Bayonet Kerrison Punch, 110 mm, 2 mm,40° up
40-020-02 B	Bajonett Kerrison Stanze, 110 mm, 2 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 110 mm, 2 mm,40° up, with ceramic coating
40-020-02 F	Bajonett Kerrison Stanze, 110 mm, 2 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 110 mm, 2 mm,40° up, with thin Footplate
40-020-03	Bajonett Kerrison Stanze, 110 mm, 3 mm,40° up	Bayonet Kerrison Punch, 110 mm, 3 mm,40° up
40-020-03 BE	Bajonett Kerrison Stanze, 110 mm, 3 mm,40° up, mit Keramikbeschichtung undAuswerfer	Bayonet Kerrison Punch, 110 mm, 3 mm,40° up, with ceramic coating andEjector
40-020-03 F	Bajonett Kerrison Stanze, 110 mm, 3 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 110 mm, 3 mm,40° up, with thin Footplate
40-020-04	Bajonett Kerrison Stanze, 110 mm, 4 mm,40° up	Bayonet Kerrison Punch, 110 mm, 4 mm,40° up
40-020-04 B	Bajonett Kerrison Stanze, 110 mm, 4 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 110 mm, 4 mm,40° up, with ceramic coating
40-020-04 BE	Bajonett Kerrison Stanze, 110 mm, 4 mm,40° up, mit Keramikbeschichtung undAuswerfer	Bayonet Kerrison Punch, 110 mm, 4 mm,40° up, with ceramic coating andEjector
40-020-04 F	Bajonett Kerrison Stanze, 110 mm, 4 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 110 mm, 4 mm,40° up, with thin Footplate
40-020-05	Bajonett Kerrison Stanze, 110 mm, 5 mm,40° up	Bayonet Kerrison Punch, 110 mm, 5 mm,40° up
40-020-05 F	Bajonett Kerrison Stanze, 110 mm, 5 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 110 mm, 5 mm,40° up, with thin Footplate
40-020-06	Bajonett Kerrison Stanze, 110 mm, 6 mm,40° up	Bayonet Kerrison Punch, 110 mm, 6 mm,40° up
40-020-06 F	Bajonett Kerrison Stanze, 110 mm, 6 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 110 mm, 6 mm,40° up, with thin Footplate
40-020-11	Bajonett Kerrison Stanze, 150 mm, 1 mm,40° up	Bayonet Kerrison Punch, 150 mm, 1 mm,40° up
40-020-11 B	Bajonett Kerrison Stanze, 150 mm, 1 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 150 mm, 1 mm,40° up, with ceramic coating
40-020-11 BF	Bajonett Kerrison Stanze, 150 mm, 1 mm,40° up, mit Keramikbeschichtung unddünner Fußplatte	Bayonet Kerrison Punch, 150 mm, 1 mm,40° up, with ceramic coating and thinfootplate
40-020-11 F	Bajonett Kerrison Stanze, 150 mm, 1 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 150 mm, 1 mm,40° up, with thin Footplate
40-020-12	Bajonett Kerrison Stanze, 150 mm, 2 mm,40° up	Bayonet Kerrison Punch, 150 mm, 2 mm,40° up
40-020-12 B	Bajonett Kerrison Stanze, 150 mm, 2 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 150 mm, 2 mm,40° up, with ceramic coating
40-020-12 BE	Bajonett Kerrison Stanze, 150 mm, 2 mm,40° up, mit Keramikbeschichtung undAuswerfer	Bayonet Kerrison Punch, 150 mm, 2 mm,40° up, with ceramic coating andEjector
40-020-12 BF	Bajonett Kerrison Stanze, 150 mm, 2 mm,40° up, mit Keramikbeschichtung unddünner Fußplatte	Bayonet Kerrison Punch, 150 mm, 2 mm,40° up, with ceramic coating and thinfootplate
40-020-12 F	Bajonett Kerrison Stanze, 150 mm, 2 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 150 mm, 2 mm,40° up, with thin Footplate
40-020-13	Bajonett Kerrison Stanze, 150 mm, 3 mm,40° up	Bayonet Kerrison Punch, 150 mm, 3 mm,40° up
40-020-13 BE	Bajonett Kerrison Stanze, 150 mm, 3 mm,40° up, mit Keramikbeschichtung undAuswerfer	Bayonet Kerrison Punch, 150 mm, 3 mm,40° up, with ceramic coating andEjector
40-020-13 BFE	Bajonett Kerrison Stanze, 150 mm, 3 mm,40° up, mit Keramikbeschichtung, dünnerFußplatte und Auswerfer	Bayonet Kerrison Punch, 150 mm, 3 mm,40° up, with ceramic coating, thinfootplate and Ejector
40-020-13 F	Bajonett Kerrison Stanze, 150 mm, 3 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 150 mm, 3 mm,40° up, with thin Footplate
40-020-14	Bajonett Kerrison Stanze, 150 mm, 4 mm,40° up	Bayonet Kerrison Punch, 150 mm, 4 mm,40° up
40-020-14 B	Bajonett Kerrison Stanze, 150 mm, 4 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 150 mm, 4 mm,40° up, with ceramic coating
40-020-14 BE	Bajonett Kerrison Stanze, 150 mm, 4 mm,40° up, mit Keramikbeschichtung undAuswerfer	Bayonet Kerrison Punch, 150 mm, 4 mm,40° up, with ceramic coating andEjector
40-020-14 F	Bajonett Kerrison Stanze, 150 mm, 4 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 150 mm, 4 mm,40° up, with thin Footplate
40-020-15	Bajonett Kerrison Stanze, 150 mm, 5 mm,40° up	Bayonet Kerrison Punch, 150 mm, 5 mm,40° up



40-020-15 BE	Bajonett Kerrison Stanze, 150 mm, 5 mm,40° up, mit Keramikbeschichtung undAuswerfer	Bayonet Kerrison Punch, 150 mm, 5 mm,40° up, with ceramic coating andEjector
40-020-15 F	Bajonett Kerrison Stanze, 150 mm, 5 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 150 mm, 5 mm,40° up, with thin Footplate
40-020-16	Bajonett Kerrison Stanze, 150 mm, 6 mm,40° up	Bayonet Kerrison Punch, 150 mm, 6 mm,40° up
40-020-16 F	Bajonett Kerrison Stanze, 150 mm, 6 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 150 mm, 6 mm,40° up, with thin Footplate
40-020-21	Bajonett Kerrison Stanze, 180 mm, 1 mm,40° up	Bayonet Kerrison Punch, 180 mm, 1 mm,40° up
40-020-21 B	Bajonett Kerrison Stanze, 180 mm, 1 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 180 mm, 1 mm,40° up, with ceramic coating
40-020-21 BF	Bajonett Kerrison Stanze, 180 mm, 1 mm,40° up, mit Keramikbeschichtung unddünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 1 mm,40° up, with ceramic coating and thinfootplate
40-020-21 F	Bajonett Kerrison Stanze, 180 mm, 1 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 1 mm,40° up, with thin Footplate
40-020-22	Bajonett Kerrison Stanze, 180 mm, 2 mm,40° up	Bayonet Kerrison Punch, 180 mm, 2 mm,40° up
40-020-22 B	Bajonett Kerrison Stanze, 180 mm, 2 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 180 mm, 2 mm,40° up, with ceramic coating
40-020-22 BE	Bajonett Kerrison Stanze, 180 mm, 2 mm,40° up, mit Keramikbeschichtung undAuswerfer	Bayonet Kerrison Punch, 180 mm, 2 mm,40° up, with ceramic coating and Ejector
40-020-22 BF	Bajonett Kerrison Stanze, 180 mm, 2 mm,40° up, mit Keramikbeschichtung unddünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 2 mm,40° up, with ceramic coating and thinfootplate
40-020-22 F	Bajonett Kerrison Stanze, 180 mm, 2 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 2 mm,40° up, with thin Footplate
40-020-23	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up	Bayonet Kerrison Punch, 180 mm, 3 mm,40° up
40-020-23 B	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 180 mm, 3 mm,40° up, with ceramic coating
40-020-23 BE	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, mit Keramikbeschichtung undAuswerfer	Bayonet Kerrison Punch, 180 mm, 3 mm,40° up, with ceramic coating and Ejector
40-020-23 BF	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, mit Keramikbeschichtung unddünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 3 mm,40° up, with ceramic coating and thinfootplate
40-020-23 BFE	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, mit Keramikbeschichtung, dünnerFußplatte und Auswerfer	Bayonet Kerrison Punch, 180 mm, 3 mm,40° up, with ceramic coating, thin foot-plate and Ejector
40-020-23 F	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 3 mm,40° up, with thin Footplate
40-020-24	Bajonett Kerrison Stanze, 180 mm, 4 mm,40° up	Bayonet Kerrison Punch, 180 mm, 4 mm,40° up
40-020-24 B	Bajonett Kerrison Stanze, 180 mm, 4 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 180 mm, 4 mm,40° up, with ceramic coating
40-020-24 BE	Bajonett Kerrison Stanze, 180 mm, 4 mm,40° up, mit Keramikbeschichtung undAuswerfer	Bayonet Kerrison Punch, 180 mm, 4 mm,40° up, with ceramic coating and Ejector
40-020-24 BF	Bajonett Kerrison Stanze, 180 mm, 4 mm,40° up, mit Keramikbeschichtung unddünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 4 mm,40° up, with ceramic coating and thinfootplate
40-020-24 F	Bajonett Kerrison Stanze, 180 mm, 4 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 4 mm,40° up, with thin Footplate
40-020-25	Bajonett Kerrison Stanze, 180 mm, 5 mm,40° up	Bayonet Kerrison Punch, 180 mm, 5 mm,40° up
40-020-25 B	Bajonett Kerrison Stanze, 180 mm, 5 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 180 mm, 5 mm,40° up, with ceramic coating
40-020-25 BF	Bajonett Kerrison Stanze, 180 mm, 5 mm,40° up, mit Keramikbeschichtung unddünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 5 mm,40° up, with ceramic coating and thinfootplate
40-020-25 F	Bajonett Kerrison Stanze, 180 mm, 5 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 5 mm,40° up, with thin Footplate
40-020-26	Bajonett Kerrison Stanze, 180 mm, 6 mm,40° up	Bayonet Kerrison Punch, 180 mm, 6 mm,40° up
40-020-26 B	Bajonett Kerrison Stanze, 180 mm, 6 mm,40° up, mit Keramikbeschichtung	Bayonet Kerrison Punch, 180 mm, 6 mm,40° up, with ceramic coating
40-020-26 F	Bajonett Kerrison Stanze, 180 mm, 6 mm,40° up, mit dünner Fußplatte	Bayonet Kerrison Punch, 180 mm, 6 mm,40° up, with thin Footplate
40-020-42	Bajonett Kerrison Stanze, 230 mm, 2 mm,40° up	Bayonet Kerrison Punch, 230 mm, 2 mm,40° up
40-020-43	Bajonett Kerrison Stanze, 230 mm, 3 mm,40° up	Bayonet Kerrison Punch, 230 mm, 3 mm,40° up
40-020-44	Bajonett Kerrison Stanze, 230 mm, 4 mm,40° up	Bayonet Kerrison Punch, 230 mm, 4 mm,40° up
40-020-45	Bajonett Kerrison Stanze, 230 mm, 5 mm,40° up	Bayonet Kerrison Punch, 230 mm, 5 mm,40° up
40-021-01	Bajonett Kerrison Stanze, 110 mm, 1 mm,90° up	Bayonett Kerrison Punch, 110 mm, 1 mm,90° up
40-021-01 B	Bajonett Kerrison Stanze, 110 mm, 1 mm,90° up, mit Keramikbeschichtung	Bayonett Kerrison Punch, 110 mm, 1 mm,90° up, with ceramic coating
40-021-02	Bajonett Kerrison Stanze, 110 mm, 2 mm,90° up	Bayonett Kerrison Punch, 110 mm, 2 mm,90° up
40-021-02 B	Bajonett Kerrison Stanze, 110 mm, 2 mm,90° up, mit Keramikbeschichtung	Bayonett Kerrison Punch, 110 mm, 2 mm,90° up, with ceramic coating
40-021-03	Bajonett Kerrison Stanze, 110 mm, 3 mm,90° up	Bayonett Kerrison Punch, 110 mm, 3 mm,90° up

40-021-03 B	Bajonett Kerrison Stanze, 110 mm, 3 mm,90° up, mit Keramikbeschichtung	Bayonett Kerrison Punch, 110 mm, 3 mm,90° up, with ceramic coating
40-021-04	Bajonett Kerrison Stanze, 110 mm, 4 mm,90° up	Bayonett Kerrison Punch, 110 mm, 4 mm,90° up
40-021-04 B	Bajonett Kerrison Stanze, 110 mm, 4 mm,90° up, mit Keramikbeschichtung	Bayonett Kerrison Punch, 110 mm, 4 mm,90° up, with ceramic coating
40-021-05	Bajonett Kerrison Stanze, 110 mm, 5 mm,90° up	Bayonett Kerrison Punch, 110 mm, 5 mm,90° up
40-021-05 B	Bajonett Kerrison Stanze, 110 mm, 5 mm,90° up, mit Keramikbeschichtung	Bayonett Kerrison Punch, 110 mm, 5 mm,90° up, with ceramic coating
40-021-06	Bajonett Kerrison Stanze, 110 mm, 6 mm,90° up	Bayonett Kerrison Punch, 110 mm, 6 mm,90° up
40-021-06 B	Bajonett Kerrison Stanze, 110 mm, 6 mm,90° up, mit Keramikbeschichtung	Bayonett Kerrison Punch, 110 mm, 6 mm,90° up, with ceramic coating
40-021-11	Bajonett Kerrison Stanze, 150 mm, 1 mm,90° up	Bayonett Kerrison Punch, 150 mm, 1 mm,90° up
40-021-12	Bajonett Kerrison Stanze, 150 mm, 2 mm,90° up	Bayonett Kerrison Punch, 150 mm, 2 mm,90° up
40-021-13	Bajonett Kerrison Stanze, 150 mm, 3 mm,90° up	Bayonett Kerrison Punch, 150 mm, 3 mm,90° up
40-021-14	Bajonett Kerrison Stanze, 150 mm, 4 mm,90° up	Bayonett Kerrison Punch, 150 mm, 4 mm,90° up
40-021-15	Bajonett Kerrison Stanze, 150 mm, 5 mm,90° up	Bayonett Kerrison Punch, 150 mm, 5 mm,90° up
40-021-16	Bajonett Kerrison Stanze, 150 mm, 6 mm,90° up	Bayonett Kerrison Punch, 150 mm, 6 mm,90° up
40-021-21	Bajonett Kerrison Stanze, 180 mm, 1 mm,90° up	Bayonett Kerrison Punch, 180 mm, 1 mm,90° up
40-021-22	Bajonett Kerrison Stanze, 180 mm, 2 mm,90° up	Bayonett Kerrison Punch, 180 mm, 2 mm,90° up
40-021-23	Bajonett Kerrison Stanze, 180 mm, 3 mm,90° up	Bayonett Kerrison Punch, 180 mm, 3 mm,90° up
40-021-23 B	Bajonett Kerrison Stanze, 180 mm, 3 mm,90° up, mit Keramikbeschichtung	Bayonett Kerrison Punch, 180 mm, 3 mm,90° up, with ceramic coating
40-021-24	Bajonett Kerrison Stanze, 180 mm, 4 mm,90° up	Bayonett Kerrison Punch, 180 mm, 4 mm,90° up
40-021-25	Bajonett Kerrison Stanze, 180 mm, 5 mm,90° up	Bayonett Kerrison Punch, 180 mm, 5 mm,90° up
40-021-26	Bajonett Kerrison Stanze, 180 mm, 6 mm,90° up	Bayonett Kerrison Punch, 180 mm, 6 mm,90° up
40-022-01	Bajonett Kerrison Stanze, 110 mm, 1 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 1 mm,40° up, curved to left
40-022-01 F	Bajonett Kerrison Stanze, 110 mm, 1 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 1 mm,40° up, curved to left, with thin Foot-plate
40-022-02	Bajonett Kerrison Stanze, 110 mm, 2 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 2 mm,40° up, curved to left
40-022-02 F	Bajonett Kerrison Stanze, 110 mm, 2 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 2 mm,40° up, curved to left, with thin Foot-plate
40-022-03	Bajonett Kerrison Stanze, 110 mm, 3 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 3 mm,40° up, curved to left
40-022-03 F	Bajonett Kerrison Stanze, 110 mm, 3 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 3 mm,40° up, curved to left, with thin Foot-plate
40-022-04	Bajonett Kerrison Stanze, 110 mm, 4 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 4 mm,40° up, curved to left
40-022-04 F	Bajonett Kerrison Stanze, 110 mm, 4 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 4 mm,40° up, curved to left, with thin Foot-plate
40-022-05	Bajonett Kerrison Stanze, 110 mm, 5 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 5 mm,40° up, curved to left
40-022-05 F	Bajonett Kerrison Stanze, 110 mm, 5 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 5 mm,40° up, curved to left, with thin Foot-plate
40-022-06	Bajonett Kerrison Stanze, 110 mm, 6 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 6 mm,40° up, curved to left
40-022-06 F	Bajonett Kerrison Stanze, 110 mm, 6 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 6 mm,40° up, curved to left, with thin Foot-plate
40-022-11	Bajonett Kerrison Stanze, 150 mm, 1 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 1 mm,40° up, curved to left
40-022-11 F	Bajonett Kerrison Stanze, 150 mm, 1 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 1 mm,40° up, curved to left, with thin Foot-plate
40-022-12	Bajonett Kerrison Stanze, 150 mm, 2 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 2 mm,40° up, curved to left
40-022-12 F	Bajonett Kerrison Stanze, 150 mm, 2 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 2 mm,40° up, curved to left, with thin Foot-plate
40-022-13	Bajonett Kerrison Stanze, 150 mm, 3 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 3 mm,40° up, curved to left
40-022-13 F	Bajonett Kerrison Stanze, 150 mm, 3 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 3 mm,40° up, curved to left, with thin Foot-plate
40-022-14	Bajonett Kerrison Stanze, 150 mm, 4 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 4 mm,40° up, curved to left
40-022-14 F	Bajonett Kerrison Stanze, 150 mm, 4 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 4 mm,40° up, curved to left, with thin Foot-plate
40-022-15	Bajonett Kerrison Stanze, 150 mm, 5 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 5 mm,40° up, curved to left

40-022-15 F	Bajonett Kerrison Stanze, 150 mm, 5 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 5 mm,40° up, curved to left, with thin Foot-plate
40-022-16	Bajonett Kerrison Stanze, 150 mm, 6 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 6 mm,40° up, curved to left
40-022-16 F	Bajonett Kerrison Stanze, 150 mm, 6 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 6 mm,40° up, curved to left, with thin Foot-plate
40-022-21	Bajonett Kerrison Stanze, 180 mm, 1 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 1 mm,40° up, curved to left
40-022-21 F	Bajonett Kerrison Stanze, 180 mm, 1 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 1 mm,40° up, curved to left, with thin Foot-plate
40-022-22	Bajonett Kerrison Stanze, 180 mm, 2 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 2 mm,40° up, curved to left
40-022-22 F	Bajonett Kerrison Stanze, 180 mm, 2 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 2 mm,40° up, curved to left, with thin Foot-plate
40-022-23	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 3 mm,40° up, curved to left
40-022-23 B	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, nach links gebogen, mit Keramik-beschichtung	Bayonett Kerrison Punch, 180 mm, 3 mm,40° up, curved to left, with ceramiccoating
40-022-23 BFE	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, nach links gebogen, mit Keramik-beschichtung dünner Fußplatte & Auswerfer	Bayonett Kerrison Punch, 180 mm, 3 mm,40° up, curved to left, with ceramiccoating, thin footplate and Ejector
40-022-23 F	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 3 mm,40° up, curved to left, with thin Foot-plate
40-022-24	Bajonett Kerrison Stanze, 180 mm, 4 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 4 mm,40° up, curved to left
40-022-24 F	Bajonett Kerrison Stanze, 180 mm, 4 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 4 mm,40° up, curved to left, with thin Foot-plate
40-022-25	Bajonett Kerrison Stanze, 180 mm, 5 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 5 mm,40° up, curved to left
40-022-25 F	Bajonett Kerrison Stanze, 180 mm, 5 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 5 mm,40° up, curved to left, with thin Foot-plate
40-022-26	Bajonett Kerrison Stanze, 180 mm, 6 mm,40° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 6 mm,40° up, curved to left
40-022-26 F	Bajonett Kerrison Stanze, 180 mm, 6 mm,40° up, nach links gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 6 mm,40° up, curved to left, with thin Foot-plate
40-022-31	Bajonett Kerrison Stanze, 110 mm, 1 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 1 mm,40° up, curved to right
40-022-31 F	Bajonett Kerrison Stanze, 110 mm, 1 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 1 mm,40° up, curved to right, with thin Foot-plate
40-022-32	Bajonett Kerrison Stanze, 110 mm, 2 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 2 mm,40° up, curved to right
40-022-32 F	Bajonett Kerrison Stanze, 110 mm, 2 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 2 mm,40° up, curved to right, with thin Foot-plate
40-022-33	Bajonett Kerrison Stanze, 110 mm, 3 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 3 mm,40° up, curved to right
40-022-33 F	Bajonett Kerrison Stanze, 110 mm, 3 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 3 mm,40° up, curved to right, with thin Foot-plate
40-022-34	Bajonett Kerrison Stanze, 110 mm, 4 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 4 mm,40° up, curved to right
40-022-34 F	Bajonett Kerrison Stanze, 110 mm, 4 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 4 mm,40° up, curved to right, with thin Foot-plate
40-022-35	Bajonett Kerrison Stanze, 110 mm, 5 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 5 mm,40° up, curved to right
40-022-35 F	Bajonett Kerrison Stanze, 110 mm, 5 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 5 mm,40° up, curved to right, with thin Foot-plate
40-022-36	Bajonett Kerrison Stanze, 110 mm, 6 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 6 mm,40° up, curved to right
40-022-36 F	Bajonett Kerrison Stanze, 110 mm, 6 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 110 mm, 6 mm,40° up, curved to right, with thin Foot-plate
40-022-41	Bajonett Kerrison Stanze, 150 mm, 1 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 1 mm,40° up, curved to right
40-022-41 F	Bajonett Kerrison Stanze, 150 mm, 1 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 1 mm,40° up, curved to right, with thin Foot-plate
40-022-42	Bajonett Kerrison Stanze, 150 mm, 2 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 2 mm,40° up, curved to right
40-022-42 F	Bajonett Kerrison Stanze, 150 mm, 2 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 2 mm,40° up, curved to right, with thin Foot-plate
40-022-43	Bajonett Kerrison Stanze, 150 mm, 3 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 3 mm,40° up, curved to right
40-022-43 F	Bajonett Kerrison Stanze, 150 mm, 3 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 3 mm,40° up, curved to right, with thin Foot-plate

40-022-44	Bajonett Kerrison Stanze, 150 mm, 4 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 4 mm,40° up, curved to right
40-022-44 F	Bajonett Kerrison Stanze, 150 mm, 4 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 4 mm,40° up, curved to right, with thin Foot-plate
40-022-45	Bajonett Kerrison Stanze, 150 mm, 5 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 5 mm,40° up, curved to right
40-022-45 F	Bajonett Kerrison Stanze, 150 mm, 5 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 5 mm,40° up, curved to right, with thin Foot-plate
40-022-46	Bajonett Kerrison Stanze, 150 mm, 6 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 6 mm,40° up, curved to right
40-022-46 F	Bajonett Kerrison Stanze, 150 mm, 6 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 150 mm, 6 mm,40° up, curved to right, with thin Foot-plate
40-022-51	Bajonett Kerrison Stanze, 180 mm, 1 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 1 mm,40° up, curved to right
40-022-51 F	Bajonett Kerrison Stanze, 180 mm, 1 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 1 mm,40° up, curved to right, with thin Foot-plate
40-022-52	Bajonett Kerrison Stanze, 180 mm, 2 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 2 mm,40° up, curved to right
40-022-52 F	Bajonett Kerrison Stanze, 180 mm, 2 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 2 mm,40° up, curved to right, with thin Foot-plate
40-022-53	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 3 mm,40° up, curved to right
40-022-53 B	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, nach rechts gebogen, mit Kerami-beschichtung	Bayonett Kerrison Punch, 180 mm, 3 mm,40° up, curved to right, with ceramiccoating
40-022-53 F	Bajonett Kerrison Stanze, 180 mm, 3 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 3 mm,40° up, curved to right, with thin Foot-plate
40-022-54	Bajonett Kerrison Stanze, 180 mm, 4 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 4 mm,40° up, curved to right
40-022-54 F	Bajonett Kerrison Stanze, 180 mm, 4 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 4 mm,40° up, curved to right, with thin Foot-plate
40-022-55	Bajonett Kerrison Stanze, 180 mm, 5 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 5 mm,40° up, curved to right
40-022-55 F	Bajonett Kerrison Stanze, 180 mm, 5 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 5 mm,40° up, curved to right, with thin Foot-plate
40-022-56	Bajonett Kerrison Stanze, 180 mm, 6 mm,40° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 6 mm,40° up, curved to right
40-022-56 F	Bajonett Kerrison Stanze, 180 mm, 6 mm,40° up, nach rechts gebogen, mit dünnerFußplatte	Bayonett Kerrison Punch, 180 mm, 6 mm,40° up, curved to right, with thin Foot-plate
40-023-01	Bajonett Kerrison Stanze, 110 mm, 1 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 1 mm,90° up, curved to left
40-023-02	Bajonett Kerrison Stanze, 110 mm, 2 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 2 mm,90° up, curved to left
40-023-03	Bajonett Kerrison Stanze, 110 mm, 3 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 3 mm,90° up, curved to left
40-023-04	Bajonett Kerrison Stanze, 110 mm, 4 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 4 mm,90° up, curved to left
40-023-05	Bajonett Kerrison Stanze, 110 mm, 5 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 5 mm,90° up, curved to left
40-023-06	Bajonett Kerrison Stanze, 110 mm, 6 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 110 mm, 6 mm,90° up, curved to left
40-023-11	Bajonett Kerrison Stanze, 150 mm, 1 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 1 mm,90° up, curved to left
40-023-12	Bajonett Kerrison Stanze, 150 mm, 2 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 2 mm,90° up, curved to left
40-023-13	Bajonett Kerrison Stanze, 150 mm, 3 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 3 mm,90° up, curved to left
40-023-14	Bajonett Kerrison Stanze, 150 mm, 4 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 4 mm,90° up, curved to left
40-023-15	Bajonett Kerrison Stanze, 150 mm, 5 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 5 mm,90° up, curved to left
40-023-16	Bajonett Kerrison Stanze, 150 mm, 6 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 150 mm, 6 mm,90° up, curved to left
40-023-21	Bajonett Kerrison Stanze, 180 mm, 1 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 1 mm,90° up, curved to left
40-023-22	Bajonett Kerrison Stanze, 180 mm, 2 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 2 mm,90° up, curved to left
40-023-23	Bajonett Kerrison Stanze, 180 mm, 3 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 3 mm,90° up, curved to left
40-023-24	Bajonett Kerrison Stanze, 180 mm, 4 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 4 mm,90° up, curved to left

40-023-25	Bajonett Kerrison Stanze, 180 mm, 5 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 5 mm,90° up, curved to left
40-023-26	Bajonett Kerrison Stanze, 180 mm, 6 mm,90° up, nach links gebogen	Bayonett Kerrison Punch, 180 mm, 6 mm,90° up, curved to left
40-023-31	Bajonett Kerrison Stanze, 110 mm, 1 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 1 mm,90° up, curved to right
40-023-32	Bajonett Kerrison Stanze, 110 mm, 2 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 2 mm,90° up, curved to right
40-023-33	Bajonett Kerrison Stanze, 110 mm, 3 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 3 mm,90° up, curved to right
40-023-34	Bajonett Kerrison Stanze, 110 mm, 4 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 4 mm,90° up, curved to right
40-023-35	Bajonett Kerrison Stanze, 110 mm, 5 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 5 mm,90° up, curved to right
40-023-36	Bajonett Kerrison Stanze, 110 mm, 6 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 110 mm, 6 mm,90° up, curved to right
40-023-41	Bajonett Kerrison Stanze, 150 mm, 1 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 1 mm,90° up, curved to right
40-023-42	Bajonett Kerrison Stanze, 150 mm, 2 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 2 mm,90° up, curved to right
40-023-43	Bajonett Kerrison Stanze, 150 mm, 3 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 3 mm,90° up, curved to right
40-023-44	Bajonett Kerrison Stanze, 150 mm, 4 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 4 mm,90° up, curved to right
40-023-45	Bajonett Kerrison Stanze, 150 mm, 5 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 5 mm,90° up, curved to right
40-023-46	Bajonett Kerrison Stanze, 150 mm, 6 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 150 mm, 6 mm,90° up, curved to right
40-023-51	Bajonett Kerrison Stanze, 180 mm, 1 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 1 mm,90° up, curved to right
40-023-52	Bajonett Kerrison Stanze, 180 mm, 2 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 2 mm,90° up, curved to right
40-023-53	Bajonett Kerrison Stanze, 180 mm, 3 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 3 mm,90° up, curved to right
40-023-54	Bajonett Kerrison Stanze, 180 mm, 4 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 4 mm,90° up, curved to right
40-023-55	Bajonett Kerrison Stanze, 180 mm, 5 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 5 mm,90° up, curved to right
40-023-56	Bajonett Kerrison Stanze, 180 mm, 6 mm,90° up, nach rechts gebogen	Bayonett Kerrison Punch, 180 mm, 6 mm,90° up, curved to right
40-024-02	Kerrison Stanze, 180 mm, 2 mm, 40° up,Schaft aufgebogen	Kerrison Punch, 180 mm, 2 mm, 40° up,shaft curved up
40-024-02 B	Kerrison Stanze, 180 mm, 2 mm, 40° up,Schaft aufgebogen, mit Keramik-beschichtung	Kerrison Punch, 180 mm, 2 mm, 40° up,shaft curved up, with ceramic coating
40-024-02 BF	Kerrison Stanze, 180 mm, 2 mm, 40° up,Schaft aufgebogen m. Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 180 mm, 2 mm, 40° up,shaft curved up with ceramic coating andthin footplate
40-024-03	Kerrison Stanze, 180 mm, 3 mm, 40° up,Schaft aufgebogen	Kerrison Punch, 180 mm, 3 mm, 40° up,shaft curved up
40-024-03 B	Kerrison Stanze, 180 mm, 3 mm, 40° up,Schaft aufgebogen, mit Keramik-beschichtung	Kerrison Punch, 180 mm, 3 mm, 40° up,shaft curved up, with ceramic coating
40-024-03 BF	Kerrison Stanze, 180 mm, 3 mm, 40° up,Schaft aufgebogen m. Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 180 mm, 3 mm, 40° up,shaft curved up with ceramic coating andthin footplate
40-024-03 F	Kerrison Stanze, 180 mm, 3 mm, 40° up,Schaft aufgebogen, mit dünner Fußplatte	Kerrison Punch, 180 mm, 3 mm, 40° up,shaft curved up, with thin footplate
40-024-04	Kerrison Stanze, 180 mm, 4 mm, 40° up,Schaft aufgebogen	Kerrison Punch, 180 mm, 4 mm, 40° up,shaft curved up
40-024-04 B	Kerrison Stanze, 180 mm, 4 mm, 40° up,Schaft aufgebogen, mit Keramik-beschichtung	Kerrison Punch, 180 mm, 4 mm, 40° up,shaft curved up, with ceramic coating
40-024-04 BF	Kerrison Stanze, 180 mm, 4 mm, 40° up,Schaft aufgebogen m. Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 180 mm, 4 mm, 40° up,shaft curved up with ceramic coating andthin footplate
40-024-04 F	Kerrison Stanze, 180 mm, 4 mm, 40° up,Schaft aufgebogen, mit dünner Fußplatte	Kerrison Punch, 180 mm, 4 mm, 40° up,shaft curved up, with thin footplate
40-024-05	Kerrison Stanze, 180 mm, 5 mm, 40° up,Schaft aufgebogen	Kerrison Punch, 180 mm, 5 mm, 40° up,shaft curved up
40-024-05 B	Kerrison Stanze, 180 mm, 5 mm, 40° up,Schaft aufgebogen, mit Keramik-beschichtung	Kerrison Punch, 180 mm, 5 mm, 40° up,shaft curved up, with ceramic coating
40-024-12	Kerrison Stanze, 200 mm, 2 mm, 40° up,Schaft aufgebogen	Kerrison Punch, 200 mm, 2 mm, 40° up,shaft curved up

40-024-12 B	Kerrison Stanze, 200 mm, 2 mm, 40° up,Schaft aufgebogen, mit Keramik-beschichtung	Kerrison Punch, 200 mm, 2 mm, 40° up,shaft curved up, with ceramic coating
40-024-12 BF	Kerrison Stanze, 200 mm, 2 mm, 40° up,Schaft aufgebogen m. Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 200 mm, 2 mm, 40° up,shaft curved up with ceramic coating andthin footplate
40-024-13	Kerrison Stanze, 200 mm, 3 mm, 40° up,Schaft aufgebogen	Kerrison Punch, 200 mm, 3 mm, 40° up,shaft curved up
40-024-13 B	Kerrison Stanze, 200 mm, 3 mm, 40° up,Schaft aufgebogen, mit Keramik-beschichtung	Kerrison Punch, 200 mm, 3 mm, 40° up,shaft curved up, with ceramic coating
40-024-13 BF	Kerrison Stanze, 200 mm, 3 mm, 40° up,Schaft aufgebogen m. Keramikbeschichtungund dünner Fußplatte	Kerrison Punch, 200 mm, 3 mm, 40° up,shaft curved up with ceramic coating andthin footplate
40-024-14	Kerrison Stanze, 200 mm, 4 mm, 40° up,Schaft aufgebogen	Kerrison Punch, 200 mm, 4 mm, 40° up,shaft curved up
40-024-14 B	Kerrison Stanze, 200 mm, 4 mm, 40° up,Schaft aufgebogen, mit Keramik-beschichtung	Kerrison Punch, 200 mm, 4 mm, 40° up,shaft curved up, with ceramic coating
40-024-15	Kerrison Stanze, 200 mm, 5 mm, 40° up,Schaft aufgebogen	Kerrison Punch, 200 mm, 5 mm, 40° up,shaft curved up
40-024-15 B	Kerrison Stanze, 200 mm, 5 mm, 40° up,Schaft aufgebogen, mit Keramik-beschichtung	Kerrison Punch, 200 mm, 5 mm, 40° up,shaft curved up, with ceramic coating
40-025-02	Kerrison Stanze, 180 mm, 2 mm, 40° down,Schaft abgebogen	Kerrison Punch, 180 mm, 2 mm, 40° down,shaft curved down
40-025-02 B	Kerrison Stanze, 180 mm, 2 mm, 40° down,Schaft abgebogen, mit Keramik-beschichtung	Kerrison Punch, 180 mm, 2 mm, 40° down,shaft curved down, with ceramic coating
40-025-03	Kerrison Stanze, 180 mm, 3 mm, 40° down,Schaft abgebogen	Kerrison Punch, 180 mm, 3 mm, 40° down,shaft curved down
40-025-03 B	Kerrison Stanze, 180 mm, 3 mm, 40° down,Schaft abgebogen, mit Keramik-beschichtung	Kerrison Punch, 180 mm, 3 mm, 40° down,shaft curved down, with ceramic coating
40-025-04	Kerrison Stanze, 180 mm, 4 mm, 40° down,Schaft abgebogen	Kerrison Punch, 180 mm, 4 mm, 40° down,shaft curved down
40-025-04 B	Kerrison Stanze, 180 mm, 4 mm, 40° down,Schaft abgebogen, mit Keramik-beschichtung	Kerrison Punch, 180 mm, 4 mm, 40° down,shaft curved down, with ceramic coating
40-025-12	Kerrison Stanze, 200 mm, 2 mm, 40° down,Schaft abgebogen	Kerrison Punch, 200 mm, 2 mm, 40° down,shaft curved down
40-025-12 B	Kerrison Stanze, 200 mm, 2 mm, 40° down,Schaft abgebogen, mit Keramik-beschichtung	Kerrison Punch, 200 mm, 2 mm, 40° down,shaft curved down, with ceramic coating
40-025-13	Kerrison Stanze, 200 mm, 3 mm, 40° down,Schaft abgebogen	Kerrison Punch, 200 mm, 3 mm, 40° down,shaft curved down
40-025-13 B	Kerrison Stanze, 200 mm, 3 mm, 40° down,Schaft abgebogen, mit Keramik-beschichtung	Kerrison Punch, 200 mm, 3 mm, 40° down,shaft curved down, with ceramic coating
40-025-14	Kerrison Stanze, 200 mm, 4 mm, 40° down,Schaft abgebogen	Kerrison Punch, 200 mm, 4 mm, 40° down,shaft curved down
40-025-14 B	Kerrison Stanze, 200 mm, 4 mm, 40° down,Schaft abgebogen, mit Keramik-beschichtung	Kerrison Punch, 200 mm, 4 mm, 40° down,shaft curved down, with ceramic coating
40-027-03	Ferris-Smith-Kerrison Stanze, 180 mm,3 mm, 90° up, mit Ringgriff	Ferris-Smith-Kerrison Punch, 180 mm,3 mm, 90° up, with Ring handle
40-027-05	Ferris-Smith-Kerrison Stanze, 180 mm,5 mm, 90° up, mit Ringgriff	Ferris-Smith-Kerrison Punch, 180 mm,5 mm, 90° up, with Ring handle
40-027-13	Ferris-Smith-Kerrison Stanze, 180 mm,3 mm, 90° down, mit Ringgriff	Ferris-Smith-Kerrison Punch, 180 mm,3 mm, 90° down, with Ring handle
40-027-15	Ferris-Smith-Kerrison Stanze, 180 mm,5 mm, 90° down, mit Ringgriff	Ferris-Smith-Kerrison Punch, 180 mm,5 mm, 90° down, with Ring handle
40-027-23	Ferris-Smith-Kerrison Stanze, 180 mm,3 mm, 40° up, mit Ringgriff	Ferris-Smith-Kerrison Punch, 180 mm,3 mm, 40° up, with Ring handle
40-027-25	Ferris-Smith-Kerrison Stanze, 180 mm,5 mm, 40° up, mit Ringgriff	Ferris-Smith-Kerrison Punch, 180 mm,5 mm, 40° up, with Ring handle
40-029-01	Colclough Stanze, 150 mm, 3 mm, 90° up	Colclough Punch, 150 mm, 3 mm, 90° up
40-029-02	Colclough Stanze, 150 mm, 5 mm, 90° up	Colclough Punch, 150 mm, 5 mm, 90° up
40-029-03	Colclough Stanze, 150 mm, 3 mm, 40° up	Colclough Punch, 150 mm, 3 mm, 40° up
40-029-03 ZB	LK Stanze, 180 mm, 3 mm, 40° upzerlegbar, mit Keramikbeschichtung,	LK Punch, 180 mm, 3 mm, 40° updetachable, with ceramic coating,
40-029-05	Colclough Stanze, 150 mm, 5 mm, 40° up	Colclough Punch, 150 mm, 5 mm, 40° up
40-029-12	Colclough Stanze, 200 mm, 2 mm, 40° up	Colclough Punch, 200 mm, 2 mm, 40° up
40-029-13	Colclough Stanze, 200 mm, 3 mm, 40° up	Colclough Punch, 200 mm, 3 mm, 40° up
40-029-13 E	Colclough Stanze, 200 mm, 3 mm, 40° upmit Auswerfer	Colclough Punch, 200 mm, 3 mm, 40° upwith Ejector
40-029-14	Colclough Stanze, 200 mm, 4 mm, 40° up	Colclough Punch, 200 mm, 4 mm, 40° up
40-029-15	Colclough Stanze, 200 mm, 5 mm, 40° up	Colclough Punch, 200 mm, 5 mm, 40° up

40-029-15 E	Colclough Stanze, 200 mm, 5 mm, 40° up mit Auswerfer	Colclough Punch, 200 mm, 5 mm, 40° up with Ejector
40-029-19	Sypert Stanze, 250 mm, 5,5 mm, 40° up	Sypert Punch, 250 mm, 5,5 mm, 40° up
40-029-22	Colclough Stanze, 200 mm, 2 mm, 90° up	Colclough Punch, 200 mm, 2 mm, 90° up
40-029-23	Colclough Stanze, 200 mm, 3 mm, 90° up	Colclough Punch, 200 mm, 3 mm, 90° up
40-029-24	Colclough Stanze, 200 mm, 4 mm, 90° up	Colclough Punch, 200 mm, 4 mm, 90° up
40-029-25	Colclough Stanze, 200 mm, 5 mm, 90° up	Colclough Punch, 200 mm, 5 mm, 90° up
40-029-25 F	Colclough Stanze, 200 mm, 5 mm, 90° up mit dünner Fußplatte	Colclough Punch, 200 mm, 5 mm, 90° up with thin footplate
40-029-53	Colclough Stanze, 150 mm, 3 mm, 90° down	Colclough Punch, 150 mm, 3 mm, 90° down
40-029-55	Colclough Stanze, 150 mm, 5 mm, 90° down	Colclough Punch, 150 mm, 5 mm, 90° down
40-029-63	Colclough Stanze, 200 mm, 3 mm, 90° down	Colclough Punch, 200 mm, 3 mm, 90° down
40-029-65	Colclough Stanze, 200 mm, 5 mm, 90° down	Colclough Punch, 200 mm, 5 mm, 90° down